



PIN ASSIGNMENT:

P1	P2
1 ——— 1	
2 ——— 2	
P3	P4
1 ——— 1	
2 ——— 2	

- Notes:**
- 100% Open, Short and Miss wire Test.
 - Contact Resistance: 2Ω Max.
 - Insulation Resistance: 5MΩ Min.
 - Hi-Pot: 300V DC/10ms.

WSW P/N	L(mm)
AK-AV500	1500±50
AK-AV501	5000±50

No.	NAME	DESCRIPTION	Q'TY	UNIT
8	TIE	BLACK L=300mm	1	PCS
7	PE BAG	CLEAR SIZE: 330*380*0.05mm PRINT BLACK "MADE IN CHINA"+"1PCS"	1/10	PCS
6	PE BAG	CLEAR SIZE: 230*280*0.05mm PRINT BLACK "MADE IN CHINA"+"1PCS"	1	PCS
5	TUBE	HEAT SHRINK TUBE OD1.5mm L=8mm BLACK	4	PCS
4	SOLDER	ROUND TIN OD1.0mm	0.16	G
3	OUT JACKET	PVC 70P COLOR BLACK	13	G
2	IN JACKET	CLARITY PE	8.4	G
1	CONN	RCA PLUG BRASS CHROME PLATED OD13mm, ID9.3*L24.5mm	4	PCS
		RCA PLUG GOLD PLATED INSULATOR COLOR WHITE	4	PCS
	CABLE	[B.C 22AWG(30/0.12)+AL/MY+B(16/7/0.12)]*2F OD6.0*12mm JACKET PVC COLOR BLACK L=1500+10/-0mm	1	PCS

RoHS compliant
Unit: mm

Scale	Free				Date	Name	Customer-No.
TOLERANCE					Drawn	04.12.2018	Segal
					Approved	04.12.2018	Segal
DIM	TOL						
		© Drawn	04.12.2018	Segal			
Angle	TOL	Id.	Modification	Date			

ASSMANN WSW-No.		AK-AV50x
Drawing-No.		
ASS 8436 CA		rev00
Replace		Sheet