



Product Description

Surveillance, CCTV, RG-6, 18 AWG solid bare copper, foam PE core, 92% bare copper braid, PVC jacket, CMG

Technical Specifications

Product Overview

Suitable Applications:	Surveillance, CCTV Came	ra				
onstruction Details						
RG Type: 6						
onductor						
Size Stranding Nom. Diameter Material						
18 AWG Solid 0.040 in	BC - Bare Copper					
nsulation						
Material Nom	. Insulation Diameter					
PE - Polyethylene (Foam) 0.18	0 in (4.57 mm)					
Duter Shield						
Outer Shield Type Materi	al Coverage					
Braid Bare Coppe	er (BC) 92%					
Duter Jacket						
Material Nom	. Diameter					
PVC - Polyvinyl Chloride 0.266	in (6.76 mm)					
Overall Cable Diameter (Nomina	I): 0.266 in (6.76 mm)					
Electrical Characteristic	S					
Electricals	Nom. Outer Shield DCR	New Organization of Organization	Now Observatoriatia lumodance	New Velocity of Dece		
Nom. Conductor DCR 6.4 Ohm/1000ft (21 Ohm/km) 2		Nom. Capacitance Cond-to-Shield 16.3 pF/ft (53.5 pF/m)	Nom. Characteristic Impedance 75 Ohm	Nom. Velocity of Prop. 83%		
/oltage						
UL Voltage Rating 300 V (CMG)						
300 V (CMG)						
Mechanical Characteris	tics					

UL Temperature	Operating	
75°C	-30°C to +75°C	

Bend Radius

Installation Min.
2.7 in

Max. Pull Tension:	56 lbs (25 kg)
Bulk Cable Weight:	37 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor, Sunlight Resistance, Aerial - Black only, When supported by messenger wire	
Sustainability:	CA Prop 65, Product Lens™, Environmental Product Declaration (EPD) Available	
Flammability / Reaction to Fire:	UL1685 FT4 Loading, Limited Smoke	
CPR Compliance:	CPR Euroclass: Eca	
NEC / UL Compliance:	CMG	
CEC / C(UL) Compliance:	CMG	
European Directive Compliance:	ctive Compliance: EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)	
UK Regulation Compliance:	UKCA Mark	
APAC Compliance:	China RoHS II (GB/T 26572-2011)	
Other Standard Compliance(s):	P-07-KA110035-MSHA	

History

```
Update and Revision:
```

Revision Number: 0.389 Revision Date: 05-05-2023

Part Numbers

Variants

ltem #	Color	Putup Type	Length	UPC
533945 010500	Black	Reel	500 ft	612825161066
533945 0101000	Black	Reel	1,000 ft	612825161059
533945 010U1000	Black	UnReel	1,000 ft	612825161042
533945 0091000	White	Reel	1,000 ft	612825161035
533945 009U1000	White	UnReel	1,000 ft	612825161028

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.