

## SEK CAB FLAT SH RND AWG28/7 20P 100m



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 09 18 020 7010  |
| Specification      | SEK CAB FLAT SH RND AWG28/7 20P 100m  |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09180207010">https://b2b.harting.com/09180207010</a> |

### Version

|                 |          |
|-----------------|----------|
| Cable length    | 100 m    |
| Number of cores | 20       |
| Core structure  | AWG 28/7 |
| Shielding       | Shielded |

### Technical characteristics

|                              |  |
|------------------------------|--|
| Impedance                    | 100 $\Omega$                                   |
| Limiting temperature         | -30 ... +75 °C unmoved<br>-20 ... +75 °C moved |
| Conductor resistance @ 20 °C | $\leq 216 \Omega/\text{km}$                    |

### Material properties

|                  |      |
|------------------|------|
| Material (cable) | PVC  |
| Colour (cable)   | Grey |

### Specifications and approvals

|                |                         |
|----------------|-------------------------|
| Specifications | UL 1581<br>UL PLCC, CL2 |
| CE             | Yes                     |

### Commercial data

|                   |        |
|-------------------|--------|
| Packaging size    | 1      |
| Net weight        | 87 g/m |
| Country of origin | USA    |



**Pushing Performance**  
Since 1945

## Commercial data

|                                |  |
|--------------------------------|--|
| European customs tariff number | 85444993                                       |
| GTIN                           | 5713140024731                                  |
| eCl@ss                         | 27061801 Data and communication cable (copper) |