

Specification Sheet

Part Number: 170-03161

Self extinguishing material does not melt and is unaffected by most acids, and provides excellent thermal stability against direct flame.

Provides excellent thermal stability.

Meets FMVSS 302 specifications for use in automotive engineering.

Material cuts with ordinary scissors which reduces assembly time.



Nomex® High Temperature Woven Sleeveing, 0.5" Dia, Green, 100 ft/bulk reel

Article Number 170-03161

Type BSNMX125B

Color Green (GN)

Quantity Per reel

Product Description A densely woven aramid fiber sleeveing, this soft and flexible material is self extinguishing and can withstand temperatures reaching up to 662°F.

Short Description Nomex® High Temperature Woven Sleeveing, 0.5" Dia, Green, 100 ft/bulk reel

Global Part Name BSNMX125B-PMPI-GN

Length L (Imperial)	100.0
Length L (Metric)	30.48
Bundle Diameter Min (Imperial)	0.31
Bundle Diameter Min (Metric)	7.9
Bundle Diameter Max (Imperial)	0.63
Bundle Diameter Max (Metric)	16.0
Diameter D (Imperial)	0.50
Diameter D (Metric)	12.7
Nominal Diameter (Imperial)	0.5
Nominal Diameter (Metric)	12.7

Material Polyaramid Polymetaphenylene Isophthalamide (PMPI)

Material Shortcut PMPI

Flammability UL VW-1

Halogen Free Yes

UV Resistant (Yes/No) No

Operating Temperature -320°F to +662°F (-196 °C to +350 °C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 100

Package Quantity (Metric) 30.48

Customs Number 5806322000

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)