

May.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

| COUNT | DESCRIPTION OF REVISIONS | BY | CHKD | DATE | COUNT | DESCRIPTION OF REVISIONS | BY | CHKD | DATE |
|-------|--------------------------|----|------|------|-------|--------------------------|----|------|------|
| △ | | | | | △ | | | | |
| △ | | | | | △ | | | | |

| | | | |
|---------------------|-----------------------------|--------------|--|
| APPLICABLE STANDARD | | | |
| RATING | OPERATING TEMPERATURE RANGE | — °C TO — °C | STORAGE TEMPERATURE RANGE — °C TO — °C |
| | VOLTAGE | — | OPERATING HUMIDITY RANGE — % TO — % |
| | CURRENT | — | APPLICABLE CABLE $\phi 5.8 +0/-0.2$ |


SPECIFICATIONS

| ITEM | TEST METHOD | REQUIREMENTS | QT | AT |
|------|-------------|--------------|----|----|
|------|-------------|--------------|----|----|

| | | | | |
|---------------------|---------------------------------------|-----------------------|--------------------------|--------------------------|
| CONSTRUCTION | | | | |
| GENERAL EXAMINATION | VISUALLY AND BY MEASURING INSTRUMENT. | ACCORDING TO DRAWING. | <input type="checkbox"/> | <input type="checkbox"/> |
| MARKING | CONFIRMED VISUALLY. | | <input type="checkbox"/> | <input type="checkbox"/> |

| | | | | | |
|---------|---------|----------|---------|----------|----------|
| REMARKS | DRAWN | DESIGNED | CHECKED | APPROVED | RELEASED |
| | 03.7.14 | 03.7.14 | 03.7.14 | 03.7.14 | |

Note QT:Qualification Test AT:Assurance Test O:Applicable Test

| | | | |
|--|----------------------------|-----------------------------|------------------------------------|
|  HIROSE ELECTRIC CO., LTD. | SPECIFICATION SHEET | | PART NO. ST 40 X - CM (5 . 8) |
| | CODE NO.(OLD) CL | DRAWING NO. ELC4 -124188 | CODE NO. CL241-0024-0 |

| |
|---|
| 1 |
| 1 |

