



VMDSC125-75-M16-55-S

Ruland VMDSC125-75-M16-55-S, Vibration Isolation Mount, 125mm OD, M16 Threaded Stud, 41mm Stud Lengths, 75mm Height, 55 Shore A Natural Rubber Jacket, Stainless Steel



Description

Ruland VMDSC125-75-M16-55-S is a vibration isolation mount with two threaded studs. It has a 125mm outside diameter, M16 threaded stud, 41mm stud lengths, and 75mm height. This vibration isolation mount is used to dampen shock loads and reduce noise and wear on industrial equipment such as motors, conveyors, compressors, fans, or pumps which allows for a safer and more pleasant working environment. It is often referred to as a sandwich mount or rubber buffer because it functions as shock or vibration isolator sandwiched between two machine components or surfaces. VMDSC125-75-M16-55-S can be mounted to the system by passing it through an unthreaded hole and securing with a nut or threading it directly into tapped holes on the components it will be mounted to. The rubber jacket is made from natural rubber which has good elasticity and is well suited for most industrial equipment. It has 55 Shore A hardness for a balance of rigidity and shock absorption. The stainless steel body allows for increased corrosion resistance. VMDSC125-75-M16-55-S is manufactured by Otto Ganter, inventoried by Ruland, and RoHS3 compliant.

Product Specifications

Outer Diameter (OD)	4.92 in (125 mm)	Height (H1)	2.95 in (75 mm)
Thread (TH)	M16 x 2.0	Plate Thickness (PT)	0.12 in (3 mm)
Stud Length (LS)	1.61 in (41 mm)	Spring Rate	3711.6 lb/in (650 N/mm)
Shore Hardness	55A (+/- 5)	Max Deflection	0.74 in (18.8 mm)
Max Axial Load	2742.67 lb (12200 N)	Geometry	Cylindrical
Rubber Material	Natural Rubber	Metal Material	Stainless Steel
Metallic Body Finish	Bright	Manufacturer	JW Winco/ Otto Ganter
Country of Origin	Hungary	Weight (lbs)	3.644200
UPC	634529364789	Tariff Code	4016.99.6000
UNSPC	31162804		

Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application.