



Position switch in compact design 40 mm wide with connection cable 2 m  
Snap-action contacts 1 NO+1 NC with roller plunger with central mounting

|  |                              |
|--|------------------------------|
| <b>product brand name</b>  | SIRIUS                       |
| <b>product designation</b>   | Mechanical position switches |
| <b>product type designation</b>  | 3SE5                         |
| suitability for use safety switch  | Yes                          |
| <b>General technical data</b>  |                              |
| product function positive opening  | Yes                          |
| insulation voltage rated value   | 400 V                        |
| <b>degree of pollution</b>   | 3                            |
| <b>surge voltage resistance rated value</b>  | 4 kV                         |
| <b>protection class IP</b>   | IP67                         |
| <b>shock resistance</b>  |                              |
| • according to IEC 60068-2-27  | 30g / 11 ms                  |
| vibration resistance according to IEC 60068-2-6  | 0.35 mm/5g                   |
| mechanical service life (switching cycles) typical   | 5 000 000                    |
| electrical endurance (switching cycles) at AC-15 at 230 V typical  | 100 000                      |
| <b>electrical endurance (switching cycles) with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 typical</b> | 500 000                      |
| <b>Electrical operating cycles in one hour with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026</b>         | 1 800                        |
| <b>thermal current</b>   | 10 A                         |
| <b>material of the enclosure of the switch head</b>  | stainless steel              |
| <b>reference code according to IEC 81346-2</b>   | B                            |
| <b>active principle</b>  | mechanical                   |
| <b>repeat accuracy</b>   | 0.05 mm                      |
| <b>Substance Prohibitance (Date)</b>   | 07/01/2006                   |
| <b>minimum actuating force in directions of actuation</b>  | 15 N                         |
| <b>length of the sensor</b>  | 70 mm                        |
| <b>width of the sensor</b>   | 40 mm                        |
| <b>design of the switching contact</b>   | mechanical                   |
| <b>operating frequency rated value</b>   | 50 ... 60 Hz                 |
| <b>number of NC contacts for auxiliary contacts</b>  | 1                            |
| <b>number of NO contacts for auxiliary contacts</b>  | 1                            |
| <b>operational current at AC-15</b>  |                              |
| • at 125 V rated value   | 6 A                          |
| • at 230 V rated value   | 3 A                          |
| <b>operational current at DC-13</b>  |                              |
| • at 125 V rated value   | 0.55 A                       |
| • at 230 V rated value   | 0.27 A                       |

|  |                                |
|--|--------------------------------|
| design of the interface for safety-related communication | without                        |
| <b>Enclosure</b>   |                                |
| design of the housing                                    | block                          |
| material of the enclosure                                | metal                          |
| coating of the enclosure                                 | painted                        |
| design of the housing according to standard              | No                             |
| material of cable sheath                                 | PVC                            |
| <b>Drive Head</b>  |                                |
| design of the actuating element                          | roller plunger                 |
| shape of the switch head                                 | roller                         |
| design of the switching function                         | snap-action contact            |
| circuit principle  | snap-action contacts           |
| number of switching contacts safety-related              | 1                              |
| <b>Connections/ Terminals</b>                            |                                |
| type of electrical connection                            | cable, 5 x 0.75mm <sup>2</sup> |
| <b>Communication/ Protocol</b>                           |                                |
| design of the interface                                  | without                        |
| <b>Ambient conditions</b>                                |                                |
| ambient temperature                                      |                                |
| • during operation                                       | -25 ... +85 °C                 |
| • during storage   | -25 ... +85 °C                 |
| explosion protection category for dust                   | none                           |
| <b>Installation/ mounting/ dimensions</b>                |                                |
| mounting position  | any                            |
| fastening method   | screw fixing                   |
| <b>Certificates/ approvals</b>                           |                                |
| General Product Approval                                 |                                |



[Confirmation](#)



[KC](#)



|                          |                           |       |
|--------------------------|---------------------------|-------|
| General Product Approval | Declaration of Conformity | other |
|--------------------------|---------------------------|-------|



[Confirmation](#)

**Further information**

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SE5423-0CD21-1EA2>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SE5423-0CD21-1EA2>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SE5423-0CD21-1EA2>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SE5423-0CD21-1EA2&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SE5423-0CD21-1EA2&lang=en)

last modified:

1/26/2022