

iTorque 52 Piece Bit Set 9-45in/lbs



iTorque 9-45 In/lbs (1.0-6.0 Nm) Digital Handle & Slotted 4.5, 5.5, 6.5, 8.0mm & Phillips #0, 1, 2, 3 & Pozidriv #0, 1, 2, 3 & Hex Inch 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16" & Hex Metric 1.5, 2.0, 2.5, 3.0, 4.0, 5.0, 6.0, 8.0mm & Torx T6, T7, T8,

SKU: 28896

Details

Handle:

Handle Range 9-45 Inch/lbs. (SKU 28889)

The intelligent torque tool, Made in Germany

For applications where recommended torque settings are important.

EN ISO 6789, BS EN 26789, ASME B107.14M

Includes Certificate of Calibration

Torque can be conveniently set directly via push button integrated in handle.

Ergonomic plastic/metal compound handle of quality, robust materials.

Handle sizes proportioned to optimize torque setting.

Distinctly audible and perceptible click signal when set torque is reached.

Compatible with all Wiha torque blades

Click Control - integrated counter records all applications. Calibration alert following 5,000 applications (normative reference value/resettable) Large digital display for simple stepless setting of torque value. Units can be simply switched - Nm ↔in.lbs / cNm ↔in.oz.

±6% Accuracy

Blade:

(SKU: 28581)

Wiha special chrome-vanadium-molybdenum tool steel

Through hardened for best wear resistance

Bit Holder fits all commonly 1/4" Drive Bits

Corrosion Protected (Not For Use in Wiha Insulated Torque Control Handles)

Bits:

Slotted 4.5, 5.5, 6.5, 8.0mm

Phillips #0, #1, #2, #3

Torx® T6, T7, T8, T9, T10, T15, T20, T25, T27, T30

Hex Inch 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16"

Hex Metric 1.5, 2.0, 2.5, 3.0, 4.0, 5.0, 6.0, 8.0mm

PoziDriv #0, #1, #2, #3, #4

Torq Set #4, #5, #6, #8

Square #1, #2, #3

Triwing #0, #1, #2, #3, #4

Stored in a high quality Metal Box