

Technical data sheet

Safety relay

Part no.: 547954

MSI-RM2B-01

Contents

- Technical data
- Electrical connection
- Operation and display



Figure can vary



Technical data

Basic data

| | |
|--------|----------|
| Series | MSI-RM2B |
|--------|----------|

Functions

| | |
|-----------|---|
| Functions | Signal conversion of electronic safety outputs on potential-free relay contacts |
| Restart | Automatic |

Characteristic parameters

| | |
|----------------------------------|---|
| Mission time T_M | 20 years, EN ISO 13849-1 |
| Category | Up to 4 (depending on the category of the upstream protective device), EN ISO 13849 |
| $B10_d$ at DC1 (ohmic load) | 10,000,000 number of cycles, (2 A, 24 V) |
| $B10_d$ at AC1 (ohmic load) | 1,300,000 number of cycles, (0.5 A, 230 V) |
| $B10_d$ at DC13 (inductive load) | 10,000,000 number of cycles, (2 A, 24 V) |
| $B10_d$ at AC15 (inductive load) | 1,300,000 number of cycles, (0.5 A, 230 V) |
| $B10_{di}$, low load | 1,860,000 number of cycles |

Electrical data

| | |
|---|--|
| Protective circuit | Fuse on switching output, upstream |
| Continuous current per current path, max. | 3 A |
| External contact fuse protection per current path | 5 A quick-action, or 3.15 A delay-action |
| Permissible input line resistance, max. | 50 Ω |

Performance data

| | |
|----------------------|------------------------|
| Supply voltage U_B | 24 V, DC, -20 ... 20 % |
|----------------------|------------------------|

Outputs

| | |
|--|------------|
| Number of safety-related switching outputs (OSSDs) | 2 Piece(s) |
|--|------------|

Safety-related switching outputs

| | |
|--------------|--------------------------------------|
| Type | Safety-related switching output OSSD |
| Voltage type | AC/DC |

Safety-related switching output 1

| | |
|-------------------|-----------|
| Switching element | Relay, NO |
|-------------------|-----------|

Safety-related switching output 2

| | |
|-------------------|-----------|
| Switching element | Relay, NO |
|-------------------|-----------|

Timing

| | |
|------------------|-------|
| Pickup delay | 20 ms |
| Regression delay | 10 ms |

Connection

| | |
|-----------------------|------------|
| Number of connections | 1 Piece(s) |
|-----------------------|------------|

Connection 1

| | |
|--------------------|----------------------|
| Function | Connection to device |
| Type of connection | Terminal |
| Type of terminal | Screw terminal |
| No. of pins | 12 -pin |

Cable properties

| | |
|---------------------------|----------------------------|
| Connection cross sections | 0.2 to 2.5 mm ² |
|---------------------------|----------------------------|

Mechanical data

| | |
|-----------------------------|-----------------------------|
| Dimension (W x H x L) | 17.5 mm x 99 mm x 114.1 mm |
| Housing material | Plastic |
| Plastic housing | PA 66 |
| Electrical contact material | AgNi10 + 5 mm Au |
| Net weight | 120 g |
| Housing color | Gray |
| Type of fastening | Snap-on mounting |
| Mechanical life time | 10,000,000 actuation cycles |

Operation and display

| | |
|-----------------|------------|
| Type of display | LED |
| Number of LEDs | 2 Piece(s) |

Environmental data

| | |
|--------------------------------|---------------|
| Ambient temperature, operation | 0 ... 50 °C |
| Ambient temperature, storage | -25 ... 70 °C |

Certifications

| | |
|----------------------|------------------------|
| Degree of protection | IP 20 |
| Protection class | II |
| Certifications | c UL US TÜV NRTL US |

Classification

| | |
|-----------------------|----------|
| Customs tariff number | 85371098 |
| ECLASS 5.1.4 | 27371800 |
| ECLASS 8.0 | 27371819 |
| ECLASS 9.0 | 27371819 |
| ECLASS 10.0 | 27371819 |
| ECLASS 11.0 | 27371819 |
| ECLASS 12.0 | 27371819 |
| ETIM 5.0 | EC001449 |
| ETIM 6.0 | EC001449 |
| ETIM 7.0 | EC001449 |

Electrical connection

Connection 1

| | |
|--------------------|----------------------|
| Function | Connection to device |
| Type of connection | Terminal |
| Type of terminal | Screw terminal |
| No. of pins | 12 -pin |

Electrical connection

| Terminal | Assignment |
|----------|--|
| 22 | Relay contact 2 IN, NC |
| 24 | Relay contact 2 IN, NO |
| 11 | Relay contact 1 OUT |
| Y1 | External device monitoring circuit (EDM) |
| n.c. | n.c. |
| Y2 | External device monitoring circuit (EDM) |
| A2 | 0 V |
| B1 | Sensor input channel 1, 24V |
| B3 | Sensor input channel 2, 24V |
| 14 | Relay contact 1 IN, NO |
| 21 | Relay contact 2 OUT |
| 12 | Relay contact 1 IN, NC |

Operation and display

| LED | Display | Meaning |
|-----|-------------------------|--------------------|
| 1 | Green, continuous light | Relay K1 picked up |
| 2 | Green, continuous light | Relay K2 picked up |