Zero Smog 4V Adhesive fume filter

Product no.: T0053661299N





- Mobile fume extraction unit, extracts contaminants at up to 4 workplaces
- > Includes F7 fine dust pre-filter and wide band gas filter (50 % active carbon / 50 % Chemisorb)
- Constant Flow Control (CFC) guarantees automatical air flow regulation for each working place independent of the connectedworkplaces, at the same time avoiding unnecessary waste of suction power and saving energy
- > Electronic filter control with optical and acoustic filter alarm enables efficient filter performance monitoring
- > A powerful, maintenance-free turbine provides continuous fume extraction



Dimensions L x W x H (mm)	345 x 325 x 505
Dimensions L x W x H (inches)	12, 59 x 12, 59 x 15, 55
Weight (approx.) in kg	19
Voltage	120 V
Power	275 VA
Noise level (distance 1 m) dB(A)	51
Max. vacuum	2700 Pa
Capacity m³/h	
Pre-filter	
Compact filter	Wide band gas filter (50 % Active carbon + 50 % Chemisorb)
Max. capacity	1–4 workstations
RS232 interface (remote control)	All system functions can be operated and remotely monitored via the RS232 port
USB port	on
WX-compatible	on

Phone: +49 (0) 7143 / 580-0 Fax.: +49 (0) 7143 / 580-108 Email: info@weller-tools.com

Web: www.weller-tools.com