

R 15-EG-13,5



Part number	09 15 000 0101
Specification	R 15-EG-13,5
HARTING eCatalogue	https://b2b.harting.com/09150000101

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Hoods/Housings
Series	R 15
Type of hood/housing	Screw mounted housing
Description of hood/housing	Straight
Version	
Locking type	Screw locking
Technical characteristics	
Limiting temperature	-40 +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65
Material properties	
Material (hood/housing)	Polycarbonate (PC)
Material (seal)	NBR
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
Fire protection on railway vehicles	EN 45545-2 (2020-08)

Page 1 / 2 | Creation date 2022-12-28 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Material properties

Requirement set with Hazard Levels	R22 (HL 1-3)
	R23 (HL 1-3)
Commercial data	
Packaging size	10
Net weight	9.96 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140021594
eCl@ss	27440224 Shell for circular connectors