MTi-620

- Small, IP51-rated VRU
- 0.2 deg roll/pitch accuracy
- Full Graphical User Interface (GUI) and Software Development Kit (SDK) available

The MTi-620 is a Vertical Reference Unit with a small form-factor design for deep integration into your application. Building on the proven MTi 600-series technology it enables a robust and easy to use orientation tracking. It is designed for easy integration and seamless interfacing with other equipment.

The MTi-620 is supported by the MT Software Suite which includes MT Manager (GUI for Windows/Linux), SDK, example codes and drivers for many platforms including ROS.



- White label and OEM integration options available
- 3D models available on request

Mechanical

 Available online via Digi-Key, Mouser, Farnell and local distributors

Sensor Fusion Performance	e
Roll, Pitch Yaw/Heading Strapdown Integration (SDI)	O.2 deg RMS unreferenced, low drift Yes
Gyroscope	
Standard full range In-run bias stability Bandwidth (-3dB) Noise Density g-sensitivity (calibr.)	- 2000 deg/s - 8 deg/h - 520 Hz - 0.007 °/s/√Hz - 0.1 °/s/g
Accelerometer	
Standard full range In-run bias stability Bandwidth (-3dB) Noise Density	– 10 g – 10 (x,y) 15(z) μg – 500 Hz – 60 μg/√Hz
Magnetometer	
Standard full range Total RMS noise Non-linearity Resolution	+/- 8 G - 1 mG - 0.2% - 0.25 mG
GNSS Receiver	
Brand Model RTCM input port	– n/a – n/a – n/a
Barometer	
Standard full range Total RMS noise Relative accuracy	- 300-1250 hPa - 1.2 Pa - +/- 8 Pa (~0.5m)

IP-rating Townsersture	IP51 -40 to 85 °C
Operating Temperature Casing material	PC-ABS
Mounting orientation ————	No restriction, full 360° in all axes
Dimensions	28x31.5x13 mm
Connector —	Main: Phoenix Contact 16 pin, 1.27 mm pitch
Weight ————	8.9 g
Certifications	CE, FCC, RoHS
Electrical	
Input voltage	4.5 to 24V
Power consumption (typ)	<0.5 W
Interfaces / IO	
Interfaces	UART, CAN, RS232
Interfaces Sync Options	UART, CAN, RS232 SyncIn, SyncOut, ClockSync
Sync Options Protocols	
Sync Options Protocols Clock drift	SyncIn, SyncOut, ClockSync Xbus, ASCII (NMEA) or CAN 10 ppm (or external)
Sync Options Protocols Clock drift Output Frequency	SyncIn, SyncOut, ClockSync Xbus, ASCII (NMEA) or CAN 10 ppm (or external) Up to 2 kHz, 400 Hz SDI
Sync Options Protocols Clock drift	SyncIn, SyncOut, ClockSync Xbus, ASCII (NMEA) or CAN 10 ppm (or external)
Sync Options Protocols Clock drift Output Frequency	SyncIn, SyncOut, ClockSync Xbus, ASCII (NMEA) or CAN 10 ppm (or external) Up to 2 kHz, 400 Hz SDI
Sync Options Protocols Clock drift Output Frequency Built-in-self test	SyncIn, SyncOut, ClockSync Xbus, ASCII (NMEA) or CAN 10 ppm (or external) Up to 2 kHz, 400 Hz SDI
Sync Options Protocols Clock drift Output Frequency Built-in-self test Software Suite	SyncIn, SyncOut, ClockSync Xbus, ASCII (NMEA) or CAN 10 ppm (or external) Up to 2 kHz, 400 Hz SDI Gyr, Acc, Mag, Baro MT Manager, Firmware updater,
Sync Options Protocols Clock drift Output Frequency Built-in-self test Software Suite GUI (Windows/Linux)	SyncIn, SyncOut, ClockSync Xbus, ASCII (NMEA) or CAN 10 ppm (or external) Up to 2 kHz, 400 Hz SDI Gyr, Acc, Mag, Baro MT Manager, Firmware updater, Magnetic Field Mapper C++, C#, Python, Matlab, Nucleo,
Sync Options Protocols Clock drift Output Frequency Built-in-self test Software Suite GUI (Windows/Linux) SDK (Example code)	SyncIn, SyncOut, ClockSync Xbus, ASCII (NMEA) or CAN 10 ppm (or external) Up to 2 kHz, 400 Hz SDI Gyr, Acc, Mag, Baro MT Manager, Firmware updater, Magnetic Field Mapper C++, C#, Python, Matlab, Nucleo, public source code

Complete and detailed specifications are available at mtidocs.xsens.com





community and knowledge base