




UDS10-7MM-6MM-SS

Ruland UDS10-7MM-6MM-SS, 7mm x 6mm Double Universal Joint, Friction Bearing, Stainless Steel, Set Screw, 15.7mm OD, 82.6mm Length





Description

Ruland UDS10-7MM-6MM-SS is a double cardan friction bearing universal joint with 7mm x 6mm bores, 15.7mm OD, 82.6mm length, and #10-32 set screws. It is ideal for applications with wide distances between shafts and can accommodate all forms of misalignment. This plain bearing double universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 90° when compared to commodity style double universal joints. UDS10-7MM-6MM-SS is made from high grade stainless steel for increased corrosion resistance. It can be combined with boot UBOOT10/15-NI-KIT to protect the joints from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This double cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

Product Specifications

| 7 mm | Small Bore (B2) | 6 mm |
|--|--|--|
| 20.8 mm | B2 Max Shaft Penetration | 20.8 mm |
| 15.7 mm | Bore Tolerance | +0.025 mm / -0.000 mm |
| 82.6 mm | Center Yoke Length (LC) | 25.4 mm |
| 28.6 mm | Hub Depth (LH) | 20.8 mm |
| #10-32 | Screw Finish | Bright |
| 48.6 Nm | Rated Torque | 9.7 Nm |
| 90° | Material Specification | Yokes: 303 Stainless Steel Pins and Blocks: 416 Stainless Steel |
| Belden Universal | Country of Origin | USA |
| LUBRIPLATE No. 1200-2 | Matching Boot Cover | UBOOT10/15-NI-KIT |
| 63452932224 | Tariff Code | 8483.60.4000 |
| 25173810 | | |
| Performance ratings are for guidance only. The user must determine suitability for a particular application. | | |
| · | | |
| | 20.8 mm 15.7 mm 82.6 mm 28.6 mm #10-32 48.6 Nm 90° Belden Universal LUBRIPLATE No. 1200-2 63452932224 25173810 Performance ratings are for gu | 20.8 mm B2 Max Shaft Penetration 15.7 mm Bore Tolerance 82.6 mm Center Yoke Length (LC) 28.6 mm Hub Depth (LH) #10-32 Screw Finish 48.6 Nm Rated Torque 90° Material Specification Belden Universal Country of Origin LUBRIPLATE No. 1200-2 Matching Boot Cover 63452932224 Tariff Code |