

# Filter regulator MS6-LFR-1/2-D7-ERV-AS

Part number: 529190

FESTO



## Data sheet

| Feature                          | Value  |
|----------------------------------|--|
| Size                             | 6  |
| Series                           | MS   |
| Actuator lock                    | Rotary knob with detent<br>can be closed with accessories                    |
| Mounting position                | Vertical +/- 5°  |
| Grade of filtration              | 40 µm  |
| Condensate drain                 | Fully automatic  |
| Structural design                | Filter regulator with pressure gauge   |
| Max. condensate volume           | 38 ml  |
| Controller function              | Outlet pressure constant<br>With secondary exhausting                        |
| Bowl guard                       | Plastic bowl guard   |
| Symbol                           | 00991587   |
| Pressure gauge                   | with pressure gauge  |
| Operating pressure               | 2 bar ... 12 bar   |
| Pressure regulation range        | 0.5 bar ... 12 bar   |
| Max. pressure hysteresis         | 0.25 bar   |
| Standard nominal flow rate       | 4500 l/min   |
| Operating medium                 | Compressed air as per ISO 8573-1:2010 [7:4:-]<br>Inert gas                   |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress  |
| LABS (PWIS) conformity           | VDMA24364-B1/B2-L  |
| Storage temperature              | -10 °C ... 60 °C   |
| For use in the food industry     | See supplementary material information                                       |
| Air quality class at the output  | Compressed air as per ISO 8573-1:2010 [7:4:4]                                |
| Temperature of medium            | -10 °C ... 60 °C   |
| Ambient temperature              | -10 °C ... 60 °C   |
| Product weight                   | 875 g  |
| Type of mounting                 | Optionally:<br>Front panel mounting<br>Line installation<br>With accessories |
| Pneumatic connection 1           | G1/2   |
| Pneumatic connection 2           | G1/2   |
| Note on materials                | RoHS-compliant   |
| Material of operator panel       | PA<br>POM  |

| <b>Feature</b>                 | <b>Value</b>      |
|--------------------------------|-------------------|
| Seals material                 | NBR               |
| Compressed air filter material | PE                |
| Housing material               | Die-cast aluminum |
| Diaphragm material             | NBR               |
| Material of bowl               | PC                |
| Separating disc material       | POM               |