## TLM.

0

4

S 5

8 6

Q20 8

♥ 9

12

13

15

16 (17)

8

## Adjustable hook clamp

Steel or stainless steel



### STANDARD EXECUTIONS

- TLM.: basic hook clamp.

- TLML: hook clamp with padlock hole. Indexes for materials and treatments to add to the above-mentioned

standard executions:

- Z: zinc-plated steel. - SST: AISI 304 stainless steel.

LEVER BODY AND CATCH BRACKET MATERIAL Zinc-plated steel.

SPECIAL EXECUTIONS ON REQUEST Adjustable hook clamps with padlock holes.









METRIC

175





TLM.Z - TLML.Z

Code	Description	Max. working load [N]	Load at breakage [N]	52
420151	TLM.Z-26/48-60+R	1500	3000	175
420153	TLML.Z-26/48-60+R	1500	3000	175
TLM.SST		INO	X STAINLESS STEEL	ETRIC


1500

3000

1588

420151	TLM.Z-26/48-60+R	
420153	TLML.Z-26/48-60+R	
TLM.SST		
420152	TLM.SST-26/48-60+R	

STA.		22
17.5	33	
82+94		
1 -	-	



#### **METRIC**

Į

Code	Description	Max. working load [N]	Load at breakage [N]	۵'۵
420161	TLN.Z-14/72-84+R	1000	2000	74

# Adjustable hook clamp

Steel

TLN.

