



External insulated cross-connector, No. of poles: 3, Mounting type: Plug in, Width: 103.12 mm, Rated current: 380 A; Colour: Yellow

### **RAL:** 1026

### **Business data**

Article number	2770.2
Article name	AQI 3/240 YE
GTIN (EAN)	4044211055004
Packaging unit	5
Quantity unit	PC
Weight per piece (not including packaging)	317.84 g
Weight per piece (including packaging)	319.2 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	2770.2
Product description	External insulated cross-connector



### **Technical data**

Dimensions	
Width	103.12 mm
Pitch size	36 mm
Ratings	
Voltage with partition, max.	1000 V
Voltage without partition, max.	1000 V
Rated current	380 A
Contamination degree	3
Connection data	
No. of poles	3
Materials	
Material	Copper
Surface	Tin-plated
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C
Further technical data	
Mounting type	Plug in
Insulation available	$\checkmark$
Touch protection is available	$\checkmark$
Number of bridged terminals	3
Environmental Product Compliance	
REACH Conform	yes
REACH Candidate Substance Note	No
RoHS Conform	yes

Media





### Accessories

#### ##INVERSE##CONTA-CONNECT

1		
	• •	
	× •	•
}		f
ļ.		Į
2		

Feed-through terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 240 mm<sup>2</sup>, Width: 36 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1126.2</u>	RK 240 BG	4044211019419	5



Ex feed-through terminal ATEX-certified, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 240 mm<sup>2</sup>, Width: 36 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1485.2	RK 240 Ex BG	4044211107888	5



Feed-through terminal for direct mount, Screw connection, Mounting surface, Rated cross-section: 240 mm<sup>2</sup>, Width: 36 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1585.2	RK 240-D BG	4044211047764	5