

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	20MAR2015	DW	CW
	B	ECR-15-018270	07DEC2015	DW	CW
	B1	ECR-17-003902	16APR2017	RL	CW
	C	ECR-21-111798	23SEP2021	WQR	CW

NOTES:

- TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 830V
RATED CURRENT: 40A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 8KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
OPERATION TEMPERATURE: $-40^{\circ}C \sim +125^{\circ}C$
WIRE RANGE: $1.5mm^2 \sim 6.0mm^2$
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.
(ORDER No. REFER TO DRAWING: T20400X20XX000)

注释:

- 技术参数:
绝缘材料: PC
额定电压: 830V
额定电流: 40A
绝缘电阻: $\geq 400M\Omega$
脉冲电压: 8KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 500次
工作温度: $-40^{\circ}C \sim +125^{\circ}C$
接线范围: $1.5mm^2 \sim 6.0mm^2$
接线类型: 冷压接
- 端子需要单独订购。
(订货号参考图面: T20400X20XX000)

T2111042201-000	HMN-004-F	HMN-004 FEMALE MODULE INSERT HMN-004模块母插
-----------------	-----------	---

PART NUMBER
料号PART DESCRIPTION
描述

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 20MAR2015

CHK David Wang 20MAR2015

APVD Chris Wang 20MAR2015

Xiang Xu 20MAR2015

PRODUCT SPEC

108-137060

APPLICATION SPEC

114-137060

WEIGHT

-

Customer Drawing

NAME

HMN-004-F

SIZE

A3

CAGE CODE

DRAWING NO

T2111042201000

RESTRICTED TO

-

SCALE

3:2

SHEET

1 OF 1

REV

C

DIMENSIONS:
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±
1 PLC	±
2 PLC	±
3 PLC	±
4 PLC	±
ANGLES	±

MATERIAL

-

FINISH

-

TE Connectivity

1470-19 (3/13)