TRIPP-LITE

Power Cord C14 to C15 - Heavy-Duty, 15A, 250V, 14 AWG, 6 ft. (1.83 m), Red

MODEL NUMBER: P018-006-ARD





Connects a PDU or UPS system with a C14 input port to network hardware, such as computers, servers and storage drives, with C15 power connectors.

Features

Safe, Reliable Power Solution

- Connects PDU or UPS system with C14 input to network hardware with C15 power connectors
- Ideal for replacing an old or lost cord
- Recommended for Cisco, HP and other C15-compatible hardware

Color-Coded Cable and Connectors

• Colored red for easy identification in crowded rack or workstation

Optimum Construction

- 14 AWG wire
- Flexible SJT jacket
- 250V/15A rating
- UL-listed

Specifications

OVERVIEW	
UPC Code	037332199188
Device Compatibility	Network Switch; UPS; PDU
Country/Region	North America

Highlights

- Easy-to-identify red SJT jacket and fully molded red ends
- Flexible 14 AWG wire for easy routing
- 250V/15A rating
- UL-listed
- Recommended for Cisco®, HP and other C15-compatible hardware

Package Includes

 P018-006-ARD Heavy-Duty Computer Power Cord, Red, 6 ft.



INPUT	1	
Maximum Input Amps	15	
Voltage Compatibility (VAC)	100-250	
PHYSICAL		
Plug Color	Red	
Cable Jacket Color	Red	
Cable Jacket Material	PVC	
Cable Jacket Rating	VW-1	
Power Cord Jacket Type	SJT	
Cable Outer Diameter (OD)	9.3mm	
Number of Conductors	3	
Wire Gauge (AWG)	14	
Wire Gauge (OD - mm²)	2.08	
Cable Length (ft.)	6	
Cable Length (m)	1.83	
Cable Length (cm)	182.88	
Shipping Dimensions (hwd / in.)	9.90 x 7.00 x 0.50	
Shipping Dimensions (hwd / cm)	25.15 x 17.78 x 1.27	
Shipping Weight (lbs.)	0.71	
Shipping Weight (kg)	0.32	
ENVIRONMENTAL		
Operating Temperature Range	-4° to 140°F (-20° to 60°C)	
Storage Temperature Range	-4° to 140°F (-20° to 60°C)	
Operating Humidity Range	10% to 65% RH	
Storage Humidity Range	10% to 65% RH	
CONNECTIONS		
Side A - Connector 1	IEC-320-C14	
Side B - Connector 1	IEC-320-C15	
FEATURES & SPECIFICATIONS		
Antibacterial	No	
Angled Plug	No	
High Voltage	Yes	



1000 Eaton Boulevard Cleveland, OH 44122 United States

Locking Plug	No	
Coiled Power Cord	No	
STANDARDS & COMPLIANCE		
Product Certifications	cUL Listed; UL Listed	
Product Compliance	RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.