

General Purpose Single Wall

Sumitube® Product Series	Product Description	Industry Certification & Approvals	AS23053 Slash Sheet	Shrink Ratio	Shrink Temp Minimum	Operating Temp Range	Colors	Size Range
A2	General Purpose Clear	RoHS	/5 Class 2	2:1	110°C	-55°C to +135°C	Clear	3/64" to 4"
A2(3X)	Thin Wall Clear	RoHS		3:1	110°C	-55°C to +135°C	Clear	1.5 to 75/25 Metric
A4	General Purpose Commercial Grade	RoHS		2:1	110°C	-55°C to +105°C	Black, White, Red Yellow, Blue, Green, Clear	3/64" to 2"
B2	General Purpose Colors	UL/CSA/RoHS	/5 Class 1 & 3	2:1	90°C	-55°C to +135°C	Black, White, Red, Yellow, Blue, Green, Violet, Gray, Orange	3/64" to 4"
B2 (Y/G) 3:1	General Purpose Colors	UL/CSA/RoHS		3:1	90°C	-55°C to +135°C	Yellow/Green striped	187/62 to 500/185 Metric
B2 (3X)	General Purpose High Shrink Ratio	UL/CSA/RoHS		3:1	90°C	-55°C to +135°C	Black, White, Red Yellow, Blue	1.5/0.5 to 102/34 Metric
B2 (4X)	General Purpose High Shrink Ratio	UL/RoHS		4:1	90°C	-55°C to +135°C	Black	1" to 4"
B2 (4XC)	General Purpose High Shrink Ratio	UL/RoHS	/5 Class 1, overexpanded	4:1	90°C	-55°C to +135°C	Black	3/4" to 2"
B6	Semi-Rigid	RoHS		2:1	135°C	-55°C to +135°C	Black, White	3/64" to 1"
F2(Z)	Thin Wall UL/CSA Surface Printed	UL/CSA/RoHS		2:1	90°C	-55°C to +125°C	Black, White, Red, Yellow, Blue	3/64" to 4"
F4(Z)	Very Thin Wall UL/CSA Surface Printed	UL/CSA/RoHS		2:1	90°C	-55°C to +125°C	Black, White, Red, Yellow	3/64" to 1"
NH	Low Smoke Low Acid Gas Halogen-Free	RoHS		2:1	115°C	-55°C to +105°C	Black, White, Red, Yellow, Blue	1/8" to 2"
NH(TW)	Low Smoke Low Acid Gas Thin Wall Halogen-Free	RoHS		2:1	115°C	-55°C to +105°C	Black, White, Red, Yellow, Blue	1/8" to 2"

