



ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETERS		A	B	C	D	E	F	G	H	I	J	K	L	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MATERIAL FLAMABILITY RATING
	MIN IN (mm)	MAX IN (mm)	IN (mm) +/- .125 (3.175mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .030 (.762mm)	IN (mm) +/- .030 (.762mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .020 (.508mm)		
AP(R,L)-07-50-FT-30	.375 (9.52mm)	1.62 (41.14mm)	7.59 (192.88mm)	.052 (1.32mm)	.17 (4.47mm)	.30 (7.64mm)	.21 (5.33mm)	.20 (5.25mm)	.79 (20.24mm)	.065 (1.65mm)	.038 (.965mm)	.54 (13.81mm)	.51 (12.95mm)	.29 (7.36mm)	50 (222)	V-2
AP(R,L)-07-50-FT-IT-30	.375 (9.52mm)	1.62 (41.14mm)	7.59 (192.88mm)	.052 (1.32mm)	.17 (4.47mm)	.30 (7.64mm)	.21 (5.33mm)	.20 (5.25mm)	.79 (20.24mm)	.065 (1.65mm)	.038 (.965mm)	.54 (13.81mm)	.51 (12.95mm)	.29 (7.36mm)	50 (222)	HB

HOLE DIAMETER: MIN: .23 IN (5.97mm) MAX: .27 IN (7.00mm)

PANEL THICKNESS: MIN: .031 IN (.80mm) MAX: .55 IN (14.00mm)



FIR TREE CABLE TIES

COLOR DESIGNATIONS:
30 = HEAT STABILIZED UV BLACK
IT-30 = IMPACT RESISTANT HEAT STABILIZED UV BLACK

MATERIAL:
NYLON 6/6 POLYAMIDE

SHEET 1 OF 1 REV.: A DRAWING NO.: FT-50-A

A 12/20/18 KT DW DW INITIAL RELEASE DRAWN BY DATE CHECK SCALE

REV DATE BY CHK APPROVE DESCRIPTION KT 12/20/2018 DW NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.
THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.