

2-Port USB/HD Cable KVM Switch with Audio/Video, Cables and USB Peripheral Sharing

MODEL NUMBER: B032-HUA2











Control 2 computers using one HDMI monitor, USB keyboard and USB mouse. Connect a USB 2.0 hub (sold separately) to share USB peripherals, such as printers and hard drives, between computers.

Features

Access and Control 2 Computers with One Keyboard/Mouse/Monitor

- · Recommended for home, office, gaming and multimedia applications
- Switch between computers using remote port selector, hotkeys or mouse wheel
- Supports video resolutions up to 1920 x 1200 (1080p)
- Supports 2.1-channel surround sound with full bass
- Listen to audio files on one computer while accessing the other
- Compliant with EDID and HDCP
- Built-in 4-ft. (1.22 m) HDMI, USB and audio cables

USB 2.0 Peripheral Sharing

 Adding an optional USB hub (sold separately) to the USB console mouse port allows connection of peripherals, such as printers, hard drives, scanners, webcams and thumb drives

Flexible Keyboard/Mouse Applications

- Console mouse port emulation/bypass supports most mouse drivers and multifunction mice
- · Works with multimedia keyboards and wireless keyboards and mice
- Supports Mac keyboard emulation

Easy Plug-and-Play Setup and Use

- · Compatible with Windows, Mac and Linux
- No external power supply, software or drivers to install
- Switches automatically to other computer when one powers off
- · Upgradable firmware
- Takes up no valuable desk space

Highlights

- Built-in 4-ft. (1.22 m) HDMI, USB and audio cables
- Supports video resolutions up to 1920 x 1200 (1080p)
- Supports 2.1-channel surround sound with full bass
- Remote, hotkey and mouse port switching
- Compatible with Windows®, Mac® and Linux®

System Requirements

- HDMI monitor
- USB keyboard
- USB mouse
- Computers with HDMI and USB ports

Package Includes

- B032-HUA2 2-Port USB/HD Cable KVM Switch
- Owner's manual



Specifications

OVERVIEW		
UPC Code	037332200396	
Technology	HDMI; Stereo Audio; USB 2.0 (High Speed)	
VIDEO		
Max Supported Video Resolution	1920 x 1200	
AUDIO		
Audio Specification	2.1 Channel Surround Sound	
INPUT		
Built-In Cable Length (ft.)	4	
Built-In Cable Length (m)	1.2	
Built-In Cable Length (in.)	48	
Built-In Cable Length (cm)	121.9	
Redundancy - Dual Power Inputs	No	
Bus Powered	Yes	
PHYSICAL		
Color	Black	
Material of Construction	Plastic	
Cable Jacket Color	Black	
Rackmountable	No	
Shipping Dimensions (hwd / in.)	2.40 x 6.70 x 9.40	
Shipping Dimensions (hwd / cm)	6.10 x 17.02 x 23.88	
Shipping Weight (lbs.)	1.20	
Shipping Weight (kg)	0.54	
Unit Dimensions (hwd / in.)	0.000 x 0.000 x 0.000	
ENVIRONMENTAL		
Operating Temperature Range	32° to 122°F (0° to 50°C)	
Storage Temperature Range	-4° to 140°F (-20° to 60°C)	
Relative Humidity	0% to 80% RH, Non-Condensing	



COMMUNICATIONS		
IP Remote Access	No	
CONNECTIONS		
Number of Ports	2	
PC/Server Connections	USB; HDMI	
Side A - Connector 1	HDMI (FEMALE)	
Side A - Connector 2	(2) USB A (FEMALE)	
Side A - Connector 3	(2) 3.5MM (FEMALE)	
Side B - Connector 1	(2) HDMI (MALE)	
Side B - Connector 2	(4) USB A (MALE)	
Side B - Connector 3	(4) 3.5MM (MALE)	
FEATURES & SPECIFICATIONS		
NIAP-Certified Secure	No	
Number of Users	1	
On-Screen Display (OSD)	No	
Port Selection	Hotkey; Mouse; Remote Selector	
Driver Required	No	
REMOTE ACCESS		
Modem Port	No	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	3-year limited warranty	



© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.