

May.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-35 °C TO +85°C (NOTE1)	STORAGE TEMPERATURE RANGE	-10 °C TO +60°C (NOTE3)	
	OPERATING HUMIDITY RANGE	20% TO 80% (NOTE2)	STORAGE HUMIDITY RANGE	40% TO 70% (NOTE3)	
	VOLTAGE	50 V AC/DC	UL-C-UL RATING	VOLTAGE	29 V AC/DC
	CURRENT	AWG26 : 1.5A AWG28 : 1.5A AWG30 : 1.0A AWG32 : 0.8A AWG34 : 0.5A	△ 2	CURRENT	AWG26-28 : 1.5A
	APPLICABLE CONNECTOR	DF57H-6P-1.2V(##)		OPERATING TEMPERATURE RANGE	-35 °C TO +75°C (NOTE1)
	APPLICABLE CONTACT	DF57-****SCF(A)			
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
MARKING	CONFIRMED VISUALLY.		X	X	
ELECTRIC CHARACTERISTICS					
INSULATION RESISTANCE	100 V DC.	100 MΩ MIN.	X	-	
VOLTAGE PROOF	500 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	-	
MECHANICAL CHARACTERISTICS					
MECHANICAL OPERATION	30 TIMES INSERTION AND EXTRACTION.	NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-	
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 10 CYCLES FOR 3 DIRECTION.	NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-	
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		X	-	
ENVIRONMENTAL CHARACTERISTICS					
DAMP HEAT(STEADY STATE)	EXPOSED AT 40 ± 2°C , 90 TO 95 %, 96 h. (AFTER LEAVING THE ROOM TEMPERATURE FOR 1-2h.)	① INSULATION RESISTANCE: 100 MΩ MIN. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-	
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55°C → +85°C TIME 30min → 30min UNDER 5 CYCLES. (THE TRANSFERRING TIME OF THE TANK IS 2-3 min) (AFTER LEAVING THE ROOM TEMPERATURE FOR 1-2h.)	① INSULATION RESISTANCE: 100 MΩ MIN. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-	
REMARKS NOTE 1: INCLUDE THE TEMPERATURE RISING BY CURRENT. NOTE 2: NO CONDENSING. NOTE 3: APPLY TO THE PACKAGED AND UNUSED PRODUCT.					
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△	1	DIS-H-00013960	HK. HAYASHI	SZ. ONO	20220616
Unless otherwise specified, refer to IEC 60512.			APPROVED	KI. AKIYAMA	20121226
			CHECKED	HK. UMEHARA	20121226
			DESIGNED	TS. KUMAZAWA	20121226
			DRAWN	TS. KUMAZAWA	20121226
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC-344747-00-00	
HRS	SPECIFICATION SHEET		PART NO.	DF57AH-6S-1.2C	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL0666-0111-2-00	△ 1/1