




## **UD28-XX-XX-F-KIT**

Ruland UD28-XX-XX-F-KIT, Machinable Bore Double Universal Joint Kit, Friction Bearing, Steel, 1.745" (44.3mm) OD, 7.750" (196.9mm) Length





## **Description**

Ruland UD28-XX-XX-F-KIT is a double cardan friction bearing universal joint kit that can be machined with a bore size and geometry of the user's choice. It has a 1.745" (44.3mm) OD and 7.750" (196.9mm) length. UD28-XX-XX-F-KIT is ideal for applications with wide distances between shafts and can accommodate all forms of misalignment. This plain bearing double universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 90° when compared to commodity style double universal joints. UD28-XX-XX-F-KIT is made from high grade alloy steel for durability and high strength. It can be combined with boot UBOOT28/44-NI-KIT to protect the joints from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This double cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

**Product Specifications** 

|   | Froduct Specifications          |  |                               |                           |
|---|---------------------------------|--|-------------------------------|---------------------------|
| Center Yoke Length (LC) 2.750 in (69.9 mm) Yoke Length (LY) 2.500 in (63.5 mm)  Hub Depth (LH) 1.610 in (40.9 mm) Max Round Bore (Inch) 0.9688 in  Max Round Bore (Metric) 24 mm Max Hex or Square Bore (Inch) 0.9375 in  Max Hex or Square Bore (Metric) 24 mm Max Blind Bore (Inch) 1.3750 in  Max Blind Bore (Metric) 34 mm Max Round Bore w/ Key (Inch) 1" Bore, 1/4" Keyway  Max Round Bore w/ Key (Metric) 25mm Bore, 8mm Keyway Peak Torque 13,050 in-lb (1,474.5 Nm)  Rated Torque 2,610 in-lb (294.9 Nm) Max Operating Angle 90°  Material Specification Alloy Steel Manufacturer Belden Universal  Country of Origin USA Weight (Ibs) 4.232000  Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT28/44-NI-KIT  UPC 634529288658 Tariff Code 8483.60.4000  UNSPC 25173810  Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular applice of the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to | B1 Max Shaft Penetration        | 1.610 in (40.9 mm)   | B2 Max Shaft Penetration      | 1.610 in (40.9 mm)        |
| Hub Depth (LH)  1.610 in (40.9 mm)  Max Round Bore (Inch)  0.9688 in  Max Round Bore (Metric)  24 mm  Max Blind Bore (Inch)  1.3750 in  Max Blind Bore (Metric)  34 mm  Max Round Bore w/ Key (Inch)  1.3750 in  Max Round Bore (Metric)  34 mm  Max Round Bore w/ Key (Inch)  1" Bore, 1/4" Keyway  Max Round Bore w/ Key (Metric)  25mm Bore, 8mm Keyway  Peak Torque  13,050 in-lb (1,474.5 Nm)  Rated Torque  2,610 in-lb (294.9 Nm)  Max Operating Angle  90°  Material Specification  Alloy Steel  Manufacturer  Belden Universal  Country of Origin  USA  Weight (Ibs)  4.232000  Recommended Lubricant  LUBRIPLATE No. 1200-2  Matching Boot Cover  UBOOT28/44-NI-KIT  UPC  634529288658  Tariff Code  8483.60.4000  UNSPC  Note 1  Performance ratings are for guidance only. The user must determine suitability for a particular applice  California to cause cancer and birth defects or other reproductive harm. For more information go to  | Joint Outer Diameter (OD)       | 1.745 in (44.3 mm)   | Length (L)                    | 7.750 in (196.9 mm)       |
| Max Round Bore (Metric)24 mmMax Hex or Square Bore (Inch)0.9375 inMax Hex or Square Bore (Metric)24 mmMax Blind Bore (Inch)1.3750 inMax Blind Bore (Metric)34 mmMax Round Bore w/ Key (Inch)1" Bore, 1/4" KeywayMax Round Bore w/ Key (Metric)25mm Bore, 8mm KeywayPeak Torque13,050 in-lb (1,474.5 Nm)Rated Torque2,610 in-lb (294.9 Nm)Max Operating Angle90°Material SpecificationAlloy SteelManufacturerBelden UniversalCountry of OriginUSAWeight (Ibs)4.232000Recommended LubricantLUBRIPLATE No. 1200-2Matching Boot CoverUBOOT28/44-NI-KITUPC634529288658Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicProp 65WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to  | Center Yoke Length (LC)         | 2.750 in (69.9 mm)   | Yoke Length (LY)              | 2.500 in (63.5 mm)        |
| Max Hex or Square Bore (Metric)24 mmMax Blind Bore (Inch)1.3750 inMax Blind Bore (Metric)34 mmMax Round Bore w/ Key (Inch)1" Bore, 1/4" KeywayMax Round Bore w/ Key (Metric)25mm Bore, 8mm KeywayPeak Torque13,050 in-lb (1,474.5 Nm)Rated Torque2,610 in-lb (294.9 Nm)Max Operating Angle90°Material SpecificationAlloy SteelManufacturerBelden UniversalCountry of OriginUSAWeight (Ibs)4.232000Recommended LubricantLUBRIPLATE No. 1200-2Matching Boot CoverUBOOT28/44-NI-KITUPC634529288658Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicProp 65AWARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to   | Hub Depth (LH)                  | 1.610 in (40.9 mm)   | Max Round Bore (Inch)         | 0.9688 in                 |
| Max Blind Bore (Metric)34 mmMax Round Bore w/ Key (Inch)1" Bore, 1/4" KeywayMax Round Bore w/ Key (Metric)25mm Bore, 8mm KeywayPeak Torque13,050 in-lb (1,474.5 Nm)Rated Torque2,610 in-lb (294.9 Nm)Max Operating Angle90°Material SpecificationAlloy SteelManufacturerBelden UniversalCountry of OriginUSAWeight (Ibs)4.232000Recommended LubricantLUBRIPLATE No. 1200-2Matching Boot CoverUBOOT28/44-NI-KITUPC634529288658Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicProp 65WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to  | Max Round Bore (Metric)         | 24 mm  | Max Hex or Square Bore (Inch) | 0.9375 in                 |
| Max Round Bore w/ Key (Metric)25mm Bore, 8mm KeywayPeak Torque13,050 in-lb (1,474.5 Nm)Rated Torque2,610 in-lb (294.9 Nm)Max Operating Angle90°Material SpecificationAlloy SteelManufacturerBelden UniversalCountry of OriginUSAWeight (lbs)4.232000Recommended LubricantLUBRIPLATE No. 1200-2Matching Boot CoverUBOOT28/44-NI-KITUPC634529288658Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicProp 65WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to  | Max Hex or Square Bore (Metric) | 24 mm  | Max Blind Bore (Inch)         | 1.3750 in                 |
| Rated Torque2,610 in-lb (294.9 Nm)Max Operating Angle90°Material SpecificationAlloy SteelManufacturerBelden UniversalCountry of OriginUSAWeight (lbs)4.232000Recommended LubricantLUBRIPLATE No. 1200-2Matching Boot CoverUBOOT28/44-NI-KITUPC634529288658Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicProp 65▲WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to  | Max Blind Bore (Metric)         | 34 mm  | Max Round Bore w/ Key (Inch)  | 1" Bore, 1/4" Keyway      |
| Material SpecificationAlloy SteelManufacturerBelden UniversalCountry of OriginUSAWeight (Ibs)4.232000Recommended LubricantLUBRIPLATE No. 1200-2Matching Boot CoverUBOOT28/44-NI-KITUPC634529288658Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicProp 65▲WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to  | Max Round Bore w/ Key (Metric)  | 25mm Bore, 8mm Keyway  | Peak Torque                   | 13,050 in-lb (1,474.5 Nm) |
| Country of Origin  Recommended Lubricant  LUBRIPLATE No. 1200-2  Matching Boot Cover  UBOOT28/44-NI-KIT  UPC  634529288658  Tariff Code  8483.60.4000  UNSPC  25173810  Performance ratings are for guidance only. The user must determine suitability for a particular applic  Prop 65  WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to   | Rated Torque                    | 2,610 in-lb (294.9 Nm)   | Max Operating Angle           | 90°                       |
| Recommended Lubricant  LUBRIPLATE No. 1200-2  Matching Boot Cover  UBOOT28/44-NI-KIT  Tariff Code  8483.60.4000  UNSPC  25173810  Performance ratings are for guidance only. The user must determine suitability for a particular application of the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to  | Material Specification          | Alloy Steel  | Manufacturer                  | Belden Universal          |
| UPC 634529288658 Tariff Code 8483.60.4000 UNSPC 25173810  Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular applic  Prop 65 AWARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to  | Country of Origin               | USA  | Weight (lbs)                  | 4.232000                  |
| UNSPC  25173810  Note 1  Performance ratings are for guidance only. The user must determine suitability for a particular applic  Prop 65  △WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to   | Recommended Lubricant           | LUBRIPLATE No. 1200-2  | Matching Boot Cover           | UBOOT28/44-NI-KIT         |
| Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular applic  Prop 65 ▲ WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to   | UPC                             | 634529288658   | Tariff Code                   | 8483.60.4000              |
| Prop 65  AWARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to  | UNSPC                           | 25173810   |                               |                           |
| California to cause cancer and birth defects or other reproductive harm. For more information go to   | Note 1                          | Performance ratings are for guidance only. The user must determine suitability for a particular application. |                               |                           |
|   | Prop 65                         | ·  |                               |                           |