



SITOP PSU8600/3AC/24VDC/40A/4X10A PN

SITOP PSU8600 3AC 40 A/4x10 A PN stabilized power supply input: 400-500 V 3 AC output: 24 V DC/40 A/4x 10 A with PN/IE connection web server integrated OPC UA server integrated \*Ex approval no longer available\*

Input	
type of the power supply network	3-phase AC
supply voltage at AC	
<ul style="list-style-type: none"> <li>• minimum rated value</li> <li>• maximum rated value</li> <li>• initial value</li> <li>• full-scale value</li> </ul>	400 V 500 V 320 V; Derating 320 ... 360 and 530 ... 575 V 575 V
design of input wide range input	Yes
operating condition of the mains buffering	at $V_{in} = 400$ V; Prioritized supply Output 1 at power failure can be selected via DIP switch
buffering time for rated value of the output current in the event of power failure minimum	15 ms
operating condition of the mains buffering	at $V_{in} = 400$ V; Prioritized supply Output 1 at power failure can be selected via DIP switch
line frequency	
<ul style="list-style-type: none"> <li>• 1 rated value</li> <li>• 2 rated value</li> </ul>	50 Hz 60 Hz
line frequency	47 ... 63 Hz
input current	
<ul style="list-style-type: none"> <li>• at rated input voltage 400 V</li> <li>• at rated input voltage 500 V</li> </ul>	2.75 A 2.2 A
current limitation of inrush current at 25 °C maximum	14 A
I <sup>2</sup> t value maximum	2.24 A <sup>2</sup> ·s
fuse protection type	none
<ul style="list-style-type: none"> <li>• in the feeder</li> </ul>	Required: 3-pole connected miniature circuit breaker 10 ... 16 A characteristic C or circuit breaker 3RV2011-1DA10 (setting 3 A) or 3RV2711-1DD10 (UL 489)
Output	
voltage curve at output	Controlled, isolated DC voltage
number of outputs	4
output voltage at DC rated value	24 V
output voltage	
<ul style="list-style-type: none"> <li>• at output 1 at DC rated value</li> <li>• at output 2 at DC rated value</li> <li>• at output 3 at DC rated value</li> <li>• at output 4 at DC rated value</li> </ul>	24 V 24 V 24 V 24 V
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	
<ul style="list-style-type: none"> <li>• on slow fluctuation of input voltage</li> <li>• on slow fluctuation of ohm loading</li> </ul>	0.2 % 0.1 %
residual ripple	

<ul style="list-style-type: none"> <li>• maximum</li> </ul>	100 mV
voltage peak	
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	200 mV
adjustable output voltage	4 ... 28 V
product function output voltage adjustable	Yes
type of output voltage setting	via potentiometer or IE/PN interface; Derating > 24 V: 4%/V; max. 240 W per output, max. 960 W overall system
display version for normal operation	3-color LED for operating state device; LED for operating mode manual/remote; 4 LEDs for communication PROFINET; 3-color LED per output for operating state output; LED green for parallel operation Output 1 and 2 / 3 and 4
type of signal at output	Relay contact (changeover contact, contact current capacity DC 60 V/0.3 A) for "Operating state OK"
behavior of the output voltage when switching on	No overshoot of Vout (soft start)
response delay maximum	1 s; Without on-delay of the outputs
type of outputs connection	Simultaneous connecting-in of all outputs after device booting or delay time of 25 ms, 100 ms or "load-optimized" for sequential cutting-in of the outputs via DIP switches can be set
voltage increase time of the output voltage	
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	500 ms
output current	
<ul style="list-style-type: none"> <li>• rated value</li> </ul>	40 A
<ul style="list-style-type: none"> <li>• per output</li> </ul>	10 A
<ul style="list-style-type: none"> <li>• at output 1 rated value</li> </ul>	10 A
<ul style="list-style-type: none"> <li>• at output 2 rated value</li> </ul>	10 A
<ul style="list-style-type: none"> <li>• at output 3 rated value</li> </ul>	10 A
<ul style="list-style-type: none"> <li>• at output 4 rated value</li> </ul>	10 A
<ul style="list-style-type: none"> <li>• rated range</li> </ul>	0 ... 40 A; +50 ... +60 °C: Derating 2.5%/K; no derating in connection with expansion module CNX8600 and total load of the outputs at the basic device max. 480 W
supplied active power typical	960 W
product feature	
<ul style="list-style-type: none"> <li>• parallel switching of outputs</li> </ul>	Yes; Parallel circuit Output 1 with 2 or Output 3 with 4 can be selected via DIP switch
<ul style="list-style-type: none"> <li>• bridging of equipment</li> </ul>	No
<b>Efficiency</b>	
efficiency in percent	93 %
power loss [W]	
<ul style="list-style-type: none"> <li>• at rated output voltage for rated value of the output current typical</li> </ul>	72 W
<ul style="list-style-type: none"> <li>• during no-load operation maximum</li> </ul>	20 W
<b>Closed-loop control</b>	
relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	0.1 %
relative control precision of the output voltage load step of resistive load 50/100/50 % typical	0.4 %
setting time	
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	10 ms
<b>Protection and monitoring</b>	
design of the overvoltage protection	max. 35 V (max. 500 ms)
property of the output short-circuit proof	Yes
design of short-circuit protection	electronic overload cut-off; optionally constant current operation can be selected for Output 4 via DIP switches
adjustable current response value current of the current-dependent overload release	0.5 ... 10 A
type of response value setting	via potentiometer or IE/PN interface
switching characteristic	
<ul style="list-style-type: none"> <li>• of the excess current</li> </ul>	Ia > 1.0 ... < 1.5 x Ia threshold permissible for 5 s; Ia limit (= 1.5 x Ia threshold) permissible for 200 ms
<ul style="list-style-type: none"> <li>• of the current limitation</li> </ul>	Ia limit (= 1.5 x Ia threshold) permissible for 5 s, afterwards Ia threshold continuous
design of the reset device/resetting mechanism	via sensor per output or IE/PN interface
remote reset function	Non-electrically isolated 24 V input (signal level "high" at > 15 V)
overcurrent overload capability in normal operation	Total system overloadable 150% Ia rated to 5 s/min

display version for overload and short circuit	3-color LED for operating state device; 3-color LED per output for operating state output
<b>Interface</b>	
design of the interface	Ethernet/PROFINET
<ul style="list-style-type: none"> <li>PROFINET protocol</li> </ul>	Yes
protocol is supported OPC UA	Yes
<b>Safety</b>	
galvanic isolation between input and output	Yes
galvanic isolation	Safety extra-low output voltage Uout acc. to EN 60950-1 and EN 50178
operating resource protection class	Class I
leakage current	
<ul style="list-style-type: none"> <li>maximum</li> </ul>	3.5 mA
protection class IP	IP20
<b>Approvals</b>	
certificate of suitability	
<ul style="list-style-type: none"> <li>CE marking</li> <li>UL approval</li> </ul>	Yes Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
<ul style="list-style-type: none"> <li>CSA approval</li> </ul>	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
<ul style="list-style-type: none"> <li>cCSAus, Class 1, Division 2</li> <li>ATEX</li> </ul>	No No
certificate of suitability	
<ul style="list-style-type: none"> <li>IECEX</li> <li>NEC Class 2</li> <li>ULhazloc approval</li> <li>FM registration</li> </ul>	No No No No
type of certification CB-certificate	Yes
certificate of suitability	
<ul style="list-style-type: none"> <li>EAC approval</li> <li>C-Tick</li> </ul>	Yes No
certificate of suitability shipbuilding approval	Yes
shipbuilding approval	ABS, DNV GL
Marine classification association	
<ul style="list-style-type: none"> <li>American Bureau of Shipping Europe Ltd. (ABS)</li> <li>French marine classification society (BV)</li> <li>DNV GL</li> <li>Lloyds Register of Shipping (LRS)</li> <li>Nippon Kaiji Kyokai (NK)</li> </ul>	Yes No Yes No No
<b>EMC</b>	
standard	
<ul style="list-style-type: none"> <li>for emitted interference</li> <li>for mains harmonics limitation</li> <li>for interference immunity</li> </ul>	EN 55022 Class B EN 61000-3-2 EN 61000-6-2
<b>environmental conditions</b>	
ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> <li>during transport</li> <li>during storage</li> </ul>	-25 ... +60 °C; with natural convection -40 ... +85 °C -40 ... +85 °C
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
<b>Mechanics</b>	
type of electrical connection	Plug-in terminals with screwed connection
<ul style="list-style-type: none"> <li>at input</li> </ul>	L1, L2, L3, PE: Plug-in terminal with 1 screwed connection each for 0.2 ... 4 mm <sup>2</sup> single-wire / fine stranded
<ul style="list-style-type: none"> <li>at output</li> </ul>	1, 2, 3, 4: Two plug-in terminals (1, 2 and 3, 4) with 2 screwed connections each for 0.2 ... 2.5 mm <sup>2</sup> ; 0 V: Plug-in terminal with 3 screwed connections for 0.2 ... 10 mm <sup>2</sup>
<ul style="list-style-type: none"> <li>for auxiliary contacts</li> </ul>	RST (Reset): Plug-in terminal (together with alarm signal) with 1 screwed connection for 0.2 ... 1.5 mm <sup>2</sup>
<ul style="list-style-type: none"> <li>for signaling contact</li> </ul>	11, 12, 14 (alarm signal): Plug-in terminal (together with Reset) with 1 screwed connection each for 0.2 ... 1.5 mm <sup>2</sup>

product function	Yes
<ul style="list-style-type: none"> <li>● removable terminal at input</li> <li>● removable terminal at output</li> </ul>	Yes
design of the interface for communication	PROFINET/Ethernet: two RJ45 sockets (2-port switch)
suitability for interaction modular system	Yes
width of the enclosure	125 mm
height of the enclosure	125 mm
depth of the enclosure	150 mm
required spacing	
<ul style="list-style-type: none"> <li>● top</li> </ul>	50 mm
<ul style="list-style-type: none"> <li>● bottom</li> </ul>	50 mm
<ul style="list-style-type: none"> <li>● left</li> </ul>	0 mm
<ul style="list-style-type: none"> <li>● right</li> </ul>	0 mm
net weight	2.6 kg
product feature of the enclosure housing can be lined up	Yes
fastening method	Snaps onto DIN rail EN 60715 35x15
electrical accessories	Expansion modules CNX8600, buffer modules BUF8600, module UPS8600
mechanical accessories	Device identification label 20 mm × 7 mm, TI-grey 3RT2900-1SB20
MTBF at 40 °C	207 612 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

