

product type designation

IWLAN panel feedthrough N-Connect/SMA Female/Female

N-Connect/SMA Female/female Panel feedthrough; cabinet bushing, 2.4 GHz and 5 GHz for wall thickness max. 5.5 mm.



electrical data	
number of electrical connections	2
type of electrical connection	N-Connect female/SMA female
transmission frequency	0 ... 6 GHz
impedance	50 Ω
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> during operation during storage during transport 	-40 ... +70 °C -40 ... +70 °C -40 ... +70 °C
protection class IP	IP67
design, dimensions and weights	
width	25.4 mm
height	25.4 mm
length	31.3 mm
net weight	35 g
standards, specifications, approvals	
certificate of suitability	
<ul style="list-style-type: none"> RoHS conformity 	Yes
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> to website: TIA Selection Tool to web page: selection aid TIA Selection Tool to the website: IWLAN to website: Industrial communication to website: Industry Mall to website: Information and Download Center to website: Selection guide for cables and connectors to website: Image database to website: CAx-Download-Manager to website: Industry Online Support 	http://www.siemens.com/tia-selection-tool http://www.siemens.com/snst http://www.siemens.com/iwlan http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter https://sie.ag/2QdlxcP http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com
last modified:	5/20/2021 