

SST-716

SST-716AT

SST-916


SST-716 Security Shield Tool 7/16" & **SST-716AT Security Shield Tool Water Tight** are used with 7/16" hex shielded F Connectors. Design includes extended 7/16" shank for ease of use with Torque Wrenches in security shield applications. Black oxide finish. Knurled handle for secure gripping and includes a steel loop for turning leverage and carrying.

Note: **SST-716AT** is designed for use where security shield applications for PPC AquaTight® EX connectors are used.

SST-916 Security Shield Tool 9/16" is used with 9/16" hex F Connectors. Nickel plated finish. Loop attachment to allow connecting to your key ring or carabiner for easy access. Shaft length 1.625".

SPECIFICATIONS	SST-716	SST-716AT	SST-916
SIZE	7/16" (11.11mm)	7/16" (11.11mm)	9/16" (14.29mm)
TYPE	Standard	Water Tight	Standard
HANDLE	Knurled	Knurled	Knurled
MATERIAL	Steel	Steel	High Carbon Alloy Steel
FINISH	Black Oxide	Black Oxide	Nickel Plated
LENGTH	2.5" (63.5mm)	2.5" (63.5mm)	1.625" (41.28mm)
WEIGHT	0.189 lbs (85.73g)	0.189 lbs (85.73g)	0.143 lbs (64.86g)
UPC NO.	811490012141	811490012158	811490016330

MADE FOR LIFE®