

## Han PushPull SCRJ WDF coupling



Image is for illustration purposes only. Please refer to product description.

Part number	09 35 242 0333
Specification	Han PushPull SCRJ WDF coupling
HARTING eCatalogue	<a href="https://b2b.harting.com/09352420333">https://b2b.harting.com/09352420333</a>

### Identification

Category	Connectors
Series	Han <sup>®</sup> PushPull (V14)
Identification	SCRJ
Element	Panel feed through
Specification	AIDA compliant
Type of contact	SC contact
Features	Intuitive locking mechanism

### Version

Shielding	Unshielded
Number of contacts	2
Locking type	PushPull
Pack contents	Without contacts

### Technical characteristics

Limiting temperature	-40 ... +70 °C
Mating cycles	≥750
Degree of protection acc. to IEC 60529	IP65 IP67

### Material properties

Material (hood/housing)	Thermoplastic
Colour (hood/housing)	Black



Pushing Performance  
Since 1945

## Material properties

Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Naphthalene

## Specifications and approvals

Specifications	IEC 61076-3-117 Variant 14 (V14) IEC 61754-24 Mating face
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
Approvals	DNV GL
PROFINET	Yes

## Commercial data

Packaging size	1
Net weight	15.62 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140054448
eCl@ss	27440114 Rectangular connector (for field assembly)