Data sheet
2751.2 QI 3 YE

Insulated cross-connector, No. of poles: 3, Mounting type: Can be screwed on, Width: 21.7 mm, Colour: Yellow

RAL: 1026

Business data

Article number	2751.2
Article name	QI 3 YE
GTIN (EAN)	4044211054878
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	6.96 g
Weight per piece (including packaging)	6.99 g
Unit of weight	G
Customs number	85389099
Country of origin	CZ
Product description	Insulated cross-connector
Colour	Yellow

Data sheet
2751.2 QI 3 YE

Technical data

Dimensions

Length	2.4 mm
Width	21.7 mm
Pitch size	8 mm

Ratings

Voltage with partition, max.	800 V
Voltage without partition, max.	400 V
Rated current	57 A
Contamination degree	3

Connection data

No. of poles	3
Screw head	Slotted
Screw threading	M 3
Tightening torque, min.	0.5 Nm
Tightening torque, max.	1 Nm

Materials

|	
Material	Copper
Surface	Tin-plated
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

Further technical data

Mounting type	Screwable
Insulation available	✓
Number of bridged terminals	3

Data sheet

2751.2 QI 3 YE

Technical data

Environmental Product Compliance

|	
REACH Conform	No
REACH Reference date	2023-01-17
REACH Candidate Substance Note	No
REACH CAS 1 Substance	LEAD
REACH CAS 1 Percent minimal	0.1 %
REACH CAS 1 Percent maximum	4 %
REACH CAS 1 Number	7439-92-1
RoHS Conform	yes
RoHS Exception rule	6c

Media

Accessories

##INVERSE##CONTA-CONNECT

Feed-through terminal for direct mount/block variant, Screw connection, Mounting type: Mounting surface, Rated cross-section: 10 mm², Colour: Beige

| Article number	Article name	GTIN (EAN)	Packaging unit
1386.2	KBL 6-10/10-D BG	4044211044275	10

Feed-through terminal/block variant, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Colour: Beige

| Article number	Article name	GTIN (EAN)	Packaging unit
1006.2	KBL 6-10 BG	4044211001414	10 ST

Feed-through terminal for direct mount/block variant, Screw connection, Mounting type: Mounting surface, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

| Article number	Article name	GTIN (EAN)	Packaging unit
1389.2	KBL 6-10-D BG	4044211044305	100

Five-wire mains-connection block, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Colour: Multi-coloured

Article number	Article name	GTIN (EAN)	Packaging unit
1525.2	FNAB 6-10	4044211046804	10 ST

Feed-through terminal/block variant, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1007.2	KBL 6-10 m.B. BG	4044211001629	10 ST

Four-wire motor-connection block, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Colour: Multi-coloured

Article number	Article name	GTIN (EAN)	Packaging unit
1522.2	VMAB 6-10	4044211046699	10 ST

##INVERSE##CONTA-CONNECT

Test disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

| Article number	Article name	GTIN (EAN)	Packaging unit
1134.2	PTK 10/DU BG	4044211020293	50 ST

Test disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1130.2	PTK 10/LT BG	4044211019853	50 ST

Test disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

| Article number	Article name	GTIN (EAN)	Packaging unit
1131.2	PTK 10/LT/STB BG	4044211019969	50 ST

Test disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1132.2	PTK 10/QT BG	4044211020071	50 ST

Test disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1133.2	PTK 10/QT/STB BG	4044211020187	50 ST

Test disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1135.2	PTK 10/DU/STB BG	4044211020408	50 ST

Test disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

| Article number	Article name	GTIN (EAN)	Packaging unit
17366.2	PTK 10/LT/HB BG	4044211185145	50 ST

##INVERSE##CONTA-CONNECT

Test disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

| Article number	Article name	GTIN (EAN)	Packaging unit
17367.2	PTK 10/LT/STB/HB BG	4044211185152	50 ST

Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

| Article number	Article name	GTIN (EAN)	Packaging unit
1168.2	RK 6-10/35/SAS BG	4044211128630	100

Feed-through terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1005.2	RK 6-10 BG	4044211001148	100

Feed-through terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Black-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
1564.2	RK 6-10/PE BKYE	4044211047351	100 ST

Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1578.2	RK 6-10/35 BG	4044211047627	100