

wire connector CU 4 units accessory for: 3VA6 150/250



| Model | |
|---|---|
| product brand name | SETRON |
| product designation | accessories |
| Product version | circular conductor terminal |
| Accessories | Wire connector |
| General technical data | |
| designation / of the terminal | TC1.3 |
| Connections according IEC | |
| stripped length | 18 mm |
| Connections according UL | |
| permissible temperature / of connectable conductor / according to UL 486A-486B | 90 °C |
| stripped length | 0.7 in |
| connectable conductor cross-section | |
| • for copper cable / solid / minimum | 14 AWG |
| • for copper cable / solid / maximum | 10 AWG |
| • for copper cable / stranded / minimum | 14 AWG |
| • for copper cable / stranded / maximum | 1/0 AWG |
| • for copper cable / finely stranded / minimum | 14 AWG |
| • for copper cable / finely stranded / maximum | 1/0 AWG |
| tightening torque / when using copper cables | |
| • solid | 14 - 10 AWG: 55 lb-in |
| • stranded | 14 - 8 AWG: 55.0 lb-in 6 - 2 AWG: 75 lb-in 1 AWG - 1/0: 120 lb-in |
| • finely stranded | 14 - 8 AWG: 55.0 lb-in 6 - 2 AWG: 75 lb-in 1 AWG - 1/0: 120 lb-in |
| Further information | |
| Information- and Downloadcenter (Catalogs, Brochures,...) | |
| http://www.siemens.com/lowvoltage/catalogs | |
| Industry Mall (Online ordering system) | |
| https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9144-0JD11 | |
| Service&Support (Manuals, Certificates, Characteristics, FAQs,...) | |
| https://support.industry.siemens.com/cs/ww/en/ps/3VA9144-0JD11 | |
| Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) | |
| http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9144-0JD11 | |
| CAX-Online-Generator | |
| http://www.siemens.com/cax | |
| Tender specifications | |
| http://www.siemens.com/specifications | |

last modified:

7/5/2022

