

Han C F crimp contact 10 mm² Au/HMC



Part number	09 32 200 6227
Specification	Han C F crimp contact 10 mm² Au/HMC
HARTING eCatalogue	https://b2b.harting.com/09322006227

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Contacts
Series	Han [®] C HMC
Type of contact	Crimp contact

Version

Manufacturing process	Gender	Female
Manufacturing process	Manufacturing process	Turned contacts

Technical characteristics

Conductor cross-section	10 mm²
Conductor cross-section	AWG 8
Operating current	≤40 A
Contact resistance	≤1 mΩ
Stripping length	15 mm
Mating cycles with other HMC components	≥10,000

Material properties

Material (contacts)	Copper alloy
Surface (contacts)	HMC gold plated
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50

Page 1 / 2 | Creation date 2023-01-04 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Material properties

REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	b51e5b97-eeb5-438b-8538-f1771d43c17d
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

Specifications and approvals

Charifications	IEC 60664-1
Specifications	IEC 61984

Commercial data

Packaging size	25
Net weight	2.5 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140187931
eCl@ss	27440204 Contact for industrial connectors