Data sheet 2753.2 QI 10 YE





Insulated cross-connector, No. of poles: 10, Mounting type: Can be screwed on, Width: 78.4 mm, Colour: Yellow

RAL: 1026

Business data

Article number	2753.2	
Article name	QI 10 YE	
GTIN (EAN)	4044211054892	
Packaging unit	10	
Quantity unit	PC	
Weight per piece (not including packaging)	24.1 g	
Weight per piece (including packaging)	24.11 g	
Unit of weight	G	
Customs number	85389099	
Country of origin	CZ	
Product description	Insulated cross-connector	
Colour	Yellow	

Data sheet 2753.2 QI 10 YE



Technical data

Dimensions		
Length	2.4 mm	
Width	78.4 mm	
Pitch size	8 mm	
Ratings		
Voltage with partition, max.	800 V	
Voltage without partition, max.	400 V	
Rated current	57 A	
Contamination degree	3	
Connection data		
No. of poles	10	
Screw head	Slotted	
Screw threading	M 3	
Tightening torque, min.	0.5 Nm	
Tightening torque, max.	1 Nm	
Materials		
Material	Copper	
Surface	Tin-plated	
Insulation housing	Polyamide 6.6	
Flammability class UL 94	V-2	
Working temperature, min.	-40 °C	
Working temperature, max.	105 °C	
Further technical data		
Mounting type	Screwable	
Insulation available	\checkmark	
Number of bridged terminals	10	

Data sheet 2753.2 QI 10 YE



Technical data

Environmental Product Compliance		
REACH Conform	No	
REACH Reference date	2023-01-17	
REACH Candidate Substance Note	No	
REACH CAS 1 Substance	LEAD	
REACH CAS 1 Percent minimal	0.1 %	
REACH CAS 1 Percent maximum	4 %	
REACH CAS 1 Number	7439-92-1	
RoHS Conform	yes	
RoHS Exception rule	6c	

Data sheet 2753.2 QI 10 YE



Media



Data sheet 2753.2 QI 10 YE



Accessories

Screwdriver

	Screwdriver with bare blade, Colour: Black-grey				
- Consult	Article number	Article name	GTIN (EAN)	Packaging unit	
	1086.0	SDB 0,6x3,5	4044211014797	1 ST	