

## NOT for Patient-Care Vicinity - UL 1363 1U Rackmount Power Strip with 12 Hospital-Grade Outlets, 15 ft. (4.57 m) Cord

MODEL NUMBER: RS1215-HG



Medical-grade rackmount power strip with long 15 ft. cord provides power distribution outside of patient-care vicinities.

### Features

#### Versatile Power Distribution Outside of Patient-Care Vicinities

- Ideal for use in rackmount, wallmount and under-counter installation in administrative areas and other areas outside of patient-care vicinities
- Unfiltered electrical pass-through makes this strip ideal for distributing alternate waveform UPS or generator power in rack enclosures and network closets
- 120V, 50/60 Hz power strip complies with UL 1363 specifications

#### Versatile Medical-Grade Solution

- 12 NEMA 5-15R-HG hospital-grade outlets provide consistent power
- 6 outlets are on front of unit, 6 are on rear of unit
- Rugged, all-metal housing for long life in demanding environments

#### Premium Safety Features

- Resettable 15A circuit breaker protects against dangerous overloads
- Illuminated on/off switch has locking safety cover to prevent accidental shut-off

#### Ready to Use Right Out of the Box

- Detachable mounting flanges are configurable for versatile mounting orientation in a rack, on a wall or under a counter

## Specifications

### Highlights

- Occupies 1U of space in a standard 19-in. rack
- Approved for use outside of patient-care vicinities
- Complies with UL 1363 specifications
- 15 ft. cord with NEMA 5-15P-HG hospital-grade plug
- 12 NEMA 5-15R-HG hospital-grade outlets

### Package Includes

- RS1215-HG UL 1363 Medical-Grade Rackmount Power Strip with 12 15A Hospital-Grade Outlets and 15 ft. Cord
- Owner's Manual

| <b>OVERVIEW</b>                              |  |
|--|--|
| UPC Code                                     | 037332099365   |
| <b>INPUT</b>                                 |  |
| Nominal Input Voltage(s) Supported           | 120V AC  |
| Recommended Electrical Service               | 15A 120V   |
| Input Plug Features                          | Hospital Grade Plug  |
| Voltage Compatibility (VAC)                  | 120  |
| Input Plug Type                              | NEMA 5-15P-HG  |
| Input Cord Length (ft.)                      | 15   |
| Right-Angle Plug                             | No   |
| Input Cord Length (m)                        | 4.57   |
| Integrated Cord Clip                         | No   |
| <b>OUTPUT</b>                                |  |
| Frequency Compatibility                      | 50 / 60 Hz   |
| Output Receptacles                           | (12) 5-15R-HG  |
| Circuit Breaker (amps)                       | 15   |
| Transformer Accommodation                    | (5) Yes  |
| Outlet Orientation                           | 6 front / 6 rear   |
| Right-Angle Outlets                          | No   |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |  |
| Switches                                     | Lighted 2 position switch controls power to all outlets                            |
| Locking Switch Cover                         | Transparent locking switch cover prevents accidental shutoff                       |
| <b>PHYSICAL</b>                              |  |
| Color  | Black  |
| Material of Construction                     | Metal  |
| Power Cord Color                             | Black  |
| Form Factors Supported                       | 1U rackmount, wallmount and undercounter installation supported                    |
| Housing Color                                | Black  |
| Included Mounting Accessories                | Rackmount flanges  |
| Mounting Holes or Slots                      | No   |
| Outlets Measurement (Center to Center)       | Distance between Front outlets = 3.28 in.; Distance between Rear outlets = 6.5 in. |
| Receptacle Color                             | White  |

|                                      |                                       |
|--------------------------------------|---------------------------------------|
| Shipping Dimensions (hwd / in.)      | 9.40 x 2.25 x 20.30                   |
| Shipping Dimensions (hwd / cm)       | 23.88 x 5.72 x 51.56                  |
| Shipping Weight (lbs.)               | 6.10                                  |
| Shipping Weight (kg)                 | 2.77                                  |
| Unit Dimensions (hwd / in.)          | 1.750 x 19.000 x 4.000                |
| Unit Dimensions (hwd / cm)           | 4.4 x 43.9 x 10.2                     |
| Unit Weight (lbs.)                   | 4.6                                   |
| Unit Weight (kg)                     | 2.09                                  |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                       |
| Antimicrobial                        | No                                    |
| Built-In Circuit Breaker             | Yes                                   |
| TVSS Grounding                       | Back panel nut and bolt grounding lug |
| Built-in Cable Management            | No                                    |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                       |
| Product Certifications               | cUL Listed; UL 1363; UL Listed        |
| Product Compliance                   | RoHS                                  |
| <b>WARRANTY &amp; SUPPORT</b>        |                                       |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty             |