



BII-4007 (BLACK)	φ2.2 (AV-0.5f)	○	59545-0002	2		
		○	59545-0001	2		
		○	59545-0000	3		
MATERIAL	INS. RANGE	CKT.1 VOID CKT.	CKT.2	CKT.3	ENG. NUMBER	NO. OF CKT.

REVISED & REDRAWN EC NO: JTR2016-0115 DRWN:YFUSHIMI CHKD:TAITO APPR:MIYAMAMOTO	REV	2016/05/30	2016/05/30	2016/05/31	QUALITY SYMBOLS ▽ <sub>A</sub> =0 ▽ <sub>B</sub> =0 ▽ <sub>C</sub> =0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 5:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
		30 OVER	±0.3	DRAWN BY HTAMURA		DATE 1997/06/27	TITLE 4.0 WATERPROOF CONN. WIRE TO SWITCH SEAL  <b>molex</b>					
		10 OVER 30 UNDER	±0.25	CHECKED BY MSAKANO		DATE 1997/06/27						
		10 UNDER	±0.2	APPROVED BY MEMOMOTO		DATE 1997/06/27						
A1	DESCRIPTION	ANGULAR ±3 °		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO. SEE CHART		DOCUMENT NO. SD-59545-001	SHEET NO. 1 OF 1			