ATGBICS 88Y6058 IBM Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m)

Brand : ATGBICS　　　　　　　　　　　**Product code:** 88Y6058-C

Product name : 88Y6058 IBM Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m)

88Y6058 IBM Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m)

ATGBICS 88Y6058 IBM Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m):

ATGBICS 88Y6058 SFP operates on standard Category 5 unshielded twisted-pair copper cabling of link lengths up to 100m. IBM 1000BASE-T SFP modules support 10/100/1000 auto negotiation and auto MDI/MDIX. Our product meets the specification of IBM 88Y6058= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.
ATGBICS 88Y6058 IBM Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m). SFP transceiver type: Copper, Maximum data transfer rate: 1250 Mbit/s, Interface type: SFP. Product colour: Silver, Housing material: Metal, Country of origin: United Kingdom. Input voltage: 3.3 V, Maximum voltage: 4 V, Power consumption (typical): 1.3 W. Width: 13.4 mm, Depth: 56.6 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box

Performance

SFP transceiver type *	Copper
Maximum data transfer rate *	1250 Mbit/s
Interface type *	SFP
Single-mode fiber (SMF) supported	✘
Multi-mode fiber (MMF) supported	✘
SFP transceiver standard	TX
Maximum transfer distance	100 m
Ethernet LAN	✔
Ethernet interface type	Gigabit Ethernet
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-TX
Auto MDI/MDI-X	✔
Digital Diagnostics Monitoring (DDM)	✘

Features

Product colour	Silver
Housing material	Metal
Plug and Play	✔
Hot-Plug support	✔
Hot-swap	✔
Easy to install	✔
Country of origin	United Kingdom
Brand compatibility	IBM

Features

Certification	CE, FCC, RoHS

Power

Input voltage	3.3 V
Maximum voltage	4 V
Power consumption (typical)	1.3 W

Operational conditions

Maximum operating temperature	70 °C
Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	5 - 85%
Storage relative humidity (H-H)	5 - 85%

Weight & dimensions

Width	13.4 mm
Depth	56.6 mm
Height	8.5 mm
Weight	24 g

Packaging data

Number of products included	1 pc(s)
Package type	Box

Technical details

Sustainability compliance	✔
Sustainability certificates	RoHS
Doesn't contain	Lead

5056468700827