




## VMS25-20-M6-55-S/5PK

Ruland VMS25-20-M6-55-S/5PK, 5 Pack Of Rubber Bumpers, 25mm OD, M6 Threaded Stud, 18mm Stud Length, 20mm Height, 55 Shore A Natural Rubber Jacket, Stainless Steel

5 pack



### Description

Ruland VMS25-20-M6-55-S/5PK is a 5 pack of rubber bumpers, each with a threaded stud. An individual rubber bumper has 25mm outside diameter, M6 threaded stud, 18mm stud length, and 20mm height. Rubber bumpers are used to dampen shock loads and reduce noise and wear on industrial equipment, machine doors, and floors or other surfaces which allows for a safer and more pleasant working environment. They are often referred to as a sandwich mount or rubber buffer because they function as a shock or vibration isolator sandwiched between two machine components or surfaces. These rubber bumpers have a cylindrical shape allowing for even distribution of shock loads. A rubber bumper can be mounted to the system by passing it through an unthreaded hole and securing with a nut or threading it directly into tapped holes on the component it will be mounted to. The rubber jacket is made from natural rubber which has good elasticity and is well suited for most industrial equipment. Rubber bumpers in this pack have 55 Shore A hardness for a balance of rigidity and shock absorption. Bodies are made from stainless steel allowing for increased corrosion resistance. These rubber bumpers are manufactured by Otto Ganter, inventoried by Ruland, and RoHS3 compliant.

### Product Specifications

<b>Outer Diameter (OD)</b>	0.98 in (25 mm)	<b>Height (H1)</b>	0.79 in (20 mm)
<b>Thread (TH)</b>	M6 x 1.0	<b>Plate Thickness (PT)</b>	0.08 in (2 mm)
<b>Stud Length (LS)</b>	0.71 in (18 mm)	<b>Spring Rate</b>	656.67 lb/in (115 N/mm)
<b>Shore Hardness</b>	55A (+/- 5)	<b>Max Deflection</b>	0.20 in (5.0 mm)
<b>Max Axial Load</b>	130.39 lb (580 N)	<b>Multipack Quantity</b>	5
<b>Geometry</b>	Cylindrical	<b>Rubber Material</b>	Natural Rubber
<b>Metal Material</b>	Stainless Steel	<b>Metallic Body Finish</b>	Bright
<b>Manufacturer</b>	JW Winco/ Otto Ganter	<b>Country of Origin</b>	Hungary
<b>Weight (lbs)</b>	0.235000	<b>UPC</b>	634529312445
<b>Tariff Code</b>	4016.99.6000	<b>UNSPC</b>	31162804
<b>Note 1</b>	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
<b>Prop 65</b>	⚠ <b>WARNING</b> This product can expose you to chemicals including Soots and Nickel (metallic)		