

## Han PushPull Power L Metal housing



Image is for illustration purposes only. Please refer to product description.

Part number	09 35 014 0301
Specification	Han PushPull Power L Metal housing
HARTING eCatalogue	<a href="https://b2b.harting.com/09350140301">https://b2b.harting.com/09350140301</a>

### Identification

Category	Connectors
Series	Han <sup>®</sup> PushPull (V14)
Type of hood/housing	Bulkhead mounted housing

### Version

Locking type	PushPull
--------------	----------

### Technical characteristics

Limiting temperature	-40 ... +70 °C
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP65 IP67

### Material properties

Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Nickel plated
Material (seal)	NBR
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained



**Pushing Performance**  
Since 1945

## Material properties

REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead
California Proposition 65 substances	Nickel
California Proposition 65 substances	Naphthalene

## Specifications and approvals

Specifications	IEC/PAS 61076-3-126
UL / CSA	UL 1059 XCFR2.E314677
	CSA-C22.2 No. 158-10 XCFR8.E314677

## Commercial data

Packaging size	1
Net weight	22.7 g
Country of origin	China
European customs tariff number	85389099
GTIN	5713140224094
eCl@ss	27440202 Shell for industrial connectors