VE-500 & VE-5000

Readability 0.1 g





VE-500

VE-5000



- · High contrast LCD screen.
- · Robust ABS housing.
- · Leveling feet.
- Multiple weighing units.









· Internal rechargeable battery.

· Large stainless steel pan.









- Standard Functions
 - · Weighing.
 - · Parts counting.
 - · Percentage weighing.

Accumulation

· RS 232 interface.

Accesories Included

· RS-232 cable.

· Calibration weight.

TECHNICAL DATA				
Mode	I	VE-500	VE-5000	
Capacity		500 g	5000 g	
Readability		0.1 g	0.1 g	
Repe	atability	±0.1 g	±0.1 g	
Linea	rity	±0.2 g	±0.2 g	
Weig	hing Units	g, ct, oz, ozt, dwt, t, N, GN, T/A/R.		
Calibration		Exte	External.	
Pan S	size	Ø 133 mm /5.2"	160 x 180 mm / 6.3" x 7.1"	
Stabi	lization Time	≤2 seconds		
Inter	face	RS-232.		
Displ	ay	LCD, digit height 19mm / 0.7"		
Hous	ing	Plástico ABS		
Oper	ating Environment	10° to 30°C / 50° to 85°F / Humidity 20% - 80%		
Over	all Dimensions	280 x 190 x 75 mm / 11" x 7.5" x 3.5"		
Powe	r Supply	110/240V, 50/60 Hz AC adapter and rechargeable battery.		
Net \	Veight	1.9 kg / 4.2 lb	2.6 kg / 6lb	
Warr	anty	1 year.		