

8 Right-Angle Outlet Vertical Power Strip, 120V, 15A, 15 ft. (4.57 m) Cord, 5-15P, 24 in.

MODEL NUMBER: PS2408RA











The PS2408RA power strip provides horizontal or vertical power distribution for rack-mount, raceway and workbench applications in a convenient 24-inch mountable housing.

Description

The PS2408RA provides a 15-amp, 120v power strip with 8 right-angle NEMA 5-15R receptacles in a rugged, all-metal, mountable housing. It allows for both vertical and horizontal mounting, making it ideal for a variety of uses including office, rack-mount, workbench, industrial and telecom applications. With a right angle NEMA 5-15P plug and 15-ft. (4.57 m) power cord, you don't have to install the PS2408RA next to outlets you already have; it can be mounted across the room and deliver reliable service where you need it most. A lighted and covered On/Off switch helps prevent accidental shut-offs, while a 15-amp circuit breaker guards against dangerous circuit overloads. Its sturdy all-metal extruded aluminum housing stands up to demanding network, laboratory or factory environments.

Features

Multi-Outlet Power Distribution

Vertical or Horizontal Moun

Extra Long Power Cord

Premium Safety Features

Heavy-Duty Housing

Specifications

| OVERVIEW | |
|----------|--------------|
| UPC Code | 037332187451 |

Highlights

- Ideal for applications needing multiple convenience outlets for powering a variety of electronic equipment
- 24-in mountable housing with 8 right-angle NEMA 5-15R receptacles, right-angle plug and a 15-ft. (4.57 m) power cord
- Lighted, covered On/Off switch and 15-amp circuit breaker
- Sturdy construction and heavyduty, all-metal housing

Package Includes

- PS2408RA Power Strip
- · Mounting hardware
- · Instruction manual



| INPUT | | |
|--|---|--|
| Nominal Input Voltage(s) Supported | 120V AC | |
| Recommended Electrical Service | 15A 120V | |
| Input Cord Gauge Type | 14 gauge; SJT | |
| Voltage Compatibility (VAC) | 120 | |
| Input Plug Type | NEMA 5-15P | |
| Input Cord Length (ft.) | 15 | |
| Right-Angle Plug | No | |
| Input Cord Length (m) | 4.57 | |
| Integrated Cord Clip | No | |
| | | |
| OUTPUT | | |
| Frequency Compatibility | 60 Hz | |
| Output Receptacles | (8) 5-15R | |
| Circuit Breaker (amps) | 15 | |
| Transformer Accommodation | (8) Yes | |
| Right-Angle Outlets | Yes | |
| Outlet Spacing | 2.48 in. | |
| USER INTERFACE, ALERTS & CONTROLS | | |
| Switches | Lighted 2 position switch controls power to all outlets | |
| Locking Switch Cover | Transparent on/off switch cover prevents accidental turn-off | |
| | | |
| PHYSICAL | | |
| Color | Silver | |
| Material of Construction | Aluminum | |
| Power Cord Color | Black | |
| Form Factors Supported | Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications | |
| Housing Color | Silver | |
| Included Mounting Accessories | Includes mounting clips | |
| Mounting Holes or Slots | No | |
| Outlets Measurement (Center to Center) | 2.48 in. | |
| Receptacle Color | Black | |
| Shipping Dimensions (hwd / in.) | 2.40 x 4.61 x 28.19 | |
| Shipping Dimensions (hwd / cm) | 6.10 x 11.71 x 71.60 | |



| Shipping Weight (lbs.) | 3.14 | |
|-------------------------------------|--------------------------------|--|
| Shipping Weight (kg) | 1.42 | |
| Unit Dimensions (hwd / in.) | 1.250 x 1.680 x 24.520 | |
| Unit Dimensions (hwd / cm) | 3.18 x 4.27 x 62.29 | |
| Unit Weight (lbs.) | 2.71 | |
| Unit Weight (kg) | 1.23 | |
| Outlet Spacing | 2.48 in. | |
| FEATURES & SPECIFICATIONS | | |
| Antimicrobial | No | |
| Built-In Circuit Breaker | Yes | |
| STANDARDS & COMPLIANCE | | |
| Product Certifications | cUL Listed; UL 1363; UL Listed | |
| Product Compliance | RoHS | |
| WARRANTY & SUPPORT | | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty | |



© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.