HellermannTyton

Specification Sheet

Part Number: 170-03043

Weave construction adjusts to twisting and flexing without creating wrinkles or bends.

Durable construction offers excellent abrasion and cut-through resistance as well as inertness to most chemicals and fungus.

Color options available to provide easy visual and safety identification of critical wiring components.

Expands to 150% of nominal diameter for fast, easy installation.

Braided Sleeving, Expandable, 0.75" Dia, PET, Black, 250 ft/bulk reel

Article Number 170-03043 Type BSP340B Color Black (BK) **Quantity Per** reel **Product Description** Designed to adjust and expand to irregular shapes, this general purpose sleeving is lightweight and offers a high tensile strength while still maintaining flexibility. This sleeving is an excellent choice for protecting wire and cable bundles from abrasion, chafing and heat degradation. Commonly used in electrial and industrial wire harnessing application where economy and durability are required for the protection of wires, cables, tubing, bundles and pneumatic hoses.



Short Description	Braided Sleeving, Expandable, 0.75" Dia, PET, Black, 250 ft/bulk reel
Global Part Name	BSP340B-PET-BK
Length L (Imperial)	250.0
Length L (Metric)	76.2
Bundle Diameter Min (Imperial)	0.5
Bundle Diameter Min (Metric)	12.7
Bundle Diameter Max (Imperial)	1.25
Bundle Diameter Max (Metric)	31.8
Diameter D (Imperial)	0.75
Diameter D (Metric)	19.1
Nominal Diameter (Imperial)	0.75
Nominal Diameter (Metric)	19.1

Material

Polyester (PET)

Material Shortcut

Flammability	FAR 25 UL 94 V-0 FMVSS 302	
Halogen Free	Yes	
UV Resistant (Yes/No)	No	
Operating Temperature	-94°F to +257°F (-70°C to +125°C)	
Reach Compliant (Article 33)	Yes	
ROHS Compliant	Yes	
UL Recognized (US)	Yes	
Package Quantity (Imperial)	250	
Package Quantity (Metric)	76.20	
Customs Number	5808100000	

© 2023 HellermannTyton. All Rights Reserved.			
Contact Us	RoHS/WEEE Compliance	Disclaimer	Terms and Conditions