

# Product data sheet

Specifications



## ClimaSys forced vent. IP54, 300m<sup>3</sup>/h, 115V, with outlet grille and filter G2

NSYCVF300M115PF

### Overview

**Lead time** Usually Ships within 4 Weeks

### Main

<b>Range</b>	ClimaSys
<b>Product name</b>	ClimaSys CV
<b>Product or component type</b>	Fan
<b>Type of filter</b>	Standard
<b>Flow rate</b>	Free flow rate with standard filter: 300 m <sup>3</sup> /h at 50 Hz Free flow rate with standard filter: 350 m <sup>3</sup> /h at 60 Hz
<b>[Us] rated supply voltage</b>	75...126 V
<b>Input voltage</b>	115 V 50/60 Hz

### Complementary

<b>Absorbed power</b>	36 W 50 Hz 36 W 60 Hz
<b>[In] rated current</b>	0.35 A 50 Hz 0.32 A 60 Hz
<b>Noise level &lt; at</b>	55...56 dB
<b>Bearing type</b>	Ball
<b>Height</b>	268 mm external:
<b>Width</b>	248 mm external:
<b>Depth</b>	116 mm external:
<b>Cut-out dimensions</b>	223 x 223 mm
<b>Net weight</b>	1.3 kg
<b>Material</b>	Outlet grille: injected thermoplastic (ASA PC)
<b>Colour</b>	Outlet grille: grey (RAL 7035)
<b>Ambient air temperature for operation</b>	-10...70 °C
<b>Ambient air temperature for storage</b>	-40...70 °C
<b>Maximum pressure</b>	158 Pa flow rate 0 m <sup>3</sup> /h
<b>Connections - terminals</b>	Faston connector

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

<b>IP degree of protection</b>	IP54
<b>Device composition</b>	1 axial motor 2 protective grille: on the front and rear surfaces 1 filter: front of axial motor 1 outlet grille: front 1 cut-out template 1 power cord
<b>Condition of use</b>	Flow rates depends on the work point, see ProClima software Surrounding environment must be relatively clean Outside temperature must be 5 °C lower than inside temperature Filter must be cleaned and replaced regularly Overfrequent filter replacement should be avoided

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	18.5 cm
<b>Package 1 Width</b>	25 cm
<b>Package 1 Length</b>	27.5 cm
<b>Package 1 Weight</b>	1.72 kg
<b>Unit Type of Package 2</b>	P12
<b>Number of Units in Package 2</b>	64
<b>Package 2 Height</b>	120 cm
<b>Package 2 Width</b>	80 cm
<b>Package 2 Length</b>	120 cm
<b>Package 2 Weight</b>	126 kg

## Offer Sustainability

<b>Sustainable offer status</b>	Green Premium product
<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>REACH free of SVHC</b>	Yes
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
<b>RoHS exemption information</b>	Yes
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Recommended replacement(s)