


VMTSC20-25-M6-40-Z/10PK

10 pack

Ruland VMTSC20-25-M6-40-Z/10PK, Vibration Isolation Mount, 20mm OD, M6 Threaded Stud, M6 Tapped Hole, 18mm Stud Length, 6mm Tapped Hole Depth, 25mm Height, 40 Shore A Natural Rubber Jacket, Steel



Description

Ruland VMTSC20-25-M6-40-Z/10PK is a 10 pack of vibration isolation mounts, each with one tapped hole and one threaded stud. An individual vibration isolation mount has 20mm outside diameter, M6 threaded stud, M6 tapped hole, 18mm stud length, 6mm tapped hole depth, and 25mm height. Vibration isolation mounts are used to dampen shock loads and reduce noise and wear on industrial equipment such as motors, conveyors, compressors, fans, or pumps which allows for a safer and more pleasant working environment. They are often referred to as a sandwich mount or rubber buffer because they function as a shock or vibration isolator sandwiched between two machine components or surfaces. The threaded stud side of a vibration isolation mount can be mounted to the system by passing it through an unthreaded hole and securing with a nut or threading it directly into tapped hole on the component it will be mounted to. The tapped hole side can be mounted to the system by threading it onto an existing stud on the component. The rubber jacket that is made from natural rubber which has good elasticity and is well suited for most industrial equipment. Vibration isolation mounts in this pack have 40 Shore A hardness for high dampening and shock absorption. Bodies are made from zinc plated steel allowing for high strength suitability in most industrial applications. These vibration isolation mounts are manufactured by Otto Ganter, inventoried by Ruland, and RoHS3 compliant.

Product Specifications

| | | | |
|-----------------------------|------------------------|-------------------------------|-----------------------|
| Outer Diameter (OD) | 0.79 in (20 mm) | Height (H1) | 0.98 in (25 mm) |
| Thread (TH) | M6 x 1.0 | Plate Thickness (PT) | 0.08 in (2 mm) |
| Stud Length (LS) | 0.71 in (18 mm) | Tapped Hole Depth (LT) | 0.24 in (6.1 mm) |
| Spring Rate | 239.83 lb/in (42 N/mm) | Shore Hardness | 40A (+/- 5) |
| Max Deflection | 0.25 in (6.4 mm) | Max Axial Load | 59.57 lb (265 N) |
| Multipack Quantity | 10 | Geometry | Cylindrical |
| Rubber Material | Natural Rubber | Metal Material | Zinc Plated Steel |
| Metallic Body Finish | Zinc-Plated | Manufacturer | JW Winco/ Otto Ganter |
| Country of Origin | Hungary | Weight (lbs) | 0.396800 |
| UPC | 634529359662 | Tariff Code | 4016.99.6000 |

| | |
|---------------|--|
| UNSPC | 31162804 |
| Note 1 | Performance ratings are for guidance only. The user must determine suitability for a particular application. |