## ATGBICS DAC-Q28-4SFP28-25G-2M Dell Compatible Direct Attach Copper Breakout Cable 100G QSFP28 to 4x25G SFP28 (2m, Passive)

Brand : ATGBICS Product code: DAC-Q28-4SFP28-25G-2M-C

**Product name :** DAC-Q28-4SFP28-25G-2M Dell Compatible Direct Attach Copper Breakout Cable 100G QSFP28 to

4x25G SFP28 (2m, Passive)

DAC-Q28-4SFP28-25G-2M Dell Compatible Direct Attach Copper Breakout Cable 100G QSFP28 to 4x25G SFP28 (2m, Passive)

ATGBICS DAC-Q28-4SFP28-25G-2M Dell Compatible Direct Attach Copper Breakout Cable 100G QSFP28 to 4x25G SFP28 (2m, Passive):

ATGBICS DAC-Q28-4SFP28-25G-2M compatible 100GBase QSFP28 to 4x25G SFP28 direct attach breakout cable operates over passive copper with a cable length of 2m. It is suitable for very short distances and provides a cost-efficient way to connect hardware within close proximity racks. This breakout cable connects to  $1 \times 100G$  QSFP+ port of a switch on one end and to  $4 \times 25G$  SFP+ ports of a switch on the other end. Our product meets the specification of Dell DAC-Q28-4SFP28-25G-2M= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards and protocols including; IEEE802.3bj, InfiniBand EDR, MSA SFF-8665 & SFF-8402.







Features		Features	
Product colour *	Black	Country of origin	United Kingdom
Cable length *	nnector 1 * QSFP28  nnector 2 * 4 x SFP+  nnector 1 gender * Male  nnector 2 gender * Male  ket material Polyvinyl chloride (PVC)  nductor material Copper  nernet interface type 100 Gigabit Ethernet  tworking standards IEEE 802.3bj  // G wire size 30  ta transfer rate 100000 Mbit/s  yg and Play	Operational conditions	
Connector 2 * Connector 1 gender * Connector 2 gender *		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 70 °C -40 - 80 °C 10 - 90% 10 - 85%
Conductor material		Packaging data	
Ethernet interface type		Quantity per pack	1 pc(s)
Networking standards		Technical details	
AWG wire size Data transfer rate Plug and Play Certification		Sustainability compliance Sustainability certificates Doesn't contain	√ RoHS Lead



5056468724847

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.