



### Main

Accessory / separate part category	Communication accessory
Accessory / Separate Part Type	Wireless access point
Accessory / separate part destination	Smart phone Phablet Variable speed drive PC Tablet PLC
Operating Distance	50...150 m

### Complementary

Range Compatibility	Altivar Machine ATV320 Altivar Machine ATV340 Altivar Process ATV600 Altivar Process ATV900 Altivar Process Modular Modicon M251 Modicon M580
Kit composition	Battery USB cable Ethernet cable Quick start guide
Function Available	Automatic detection
Connector type	Female RJ45 automatic negotiation of 10/100 Mbit/s Micro USB type A female
Communication Port Protocol	DHCP PPPoE (Point-to-Point Protocol over Ethernet) Ethernet TCP/IP ICMP
Method of access	CSMA/CA
Operating System	Windows 7 Mac iOS Android Windows XP Windows 8 Windows Vista Windows 10
System Requirements	Google Chrome Microsoft internet explorer Apple Safari Firefox
Supply	Rechargeable internal battery
Local signalling	For Ethernet port activity LEDs (green/red) For Wi-Fi ON 1 LED (blue/orange) For battery status 1 LED (green/red) For power supply 1 LED (green)
Net Weight	0.56 lb(US) (0.255 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

IP Degree of Protection	IP20
Ambient air temperature for operation	32...104 °F (0...40 °C)
Ambient Air Temperature for Storage	32...104 °F (0...40 °C)
Standards	IEEE 802.11g IEEE 802.11n IEEE 802.3 IEEE 802.3u IEEE 802.11b
Product Certifications	FCC CE IC

## Ordering and shipping details

GTIN	3606481907004
Nbr. of units in pkg.	1
Package weight(Lbs)	8.99 oz (255 g)

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.80 in (7.1 cm)
Package 1 width	3.78 in (9.6 cm)
Package 1 Length	5.83 in (14.8 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	24
Package 2 Weight	15.27 lb(US) (6.928 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Unit Type of Package 3	P06
Number of Units in Package 3	288
Package 3 Weight	198.72 lb(US) (90.136 kg)
Package 3 Height	41.34 in (105 cm)
Package 3 width	23.62 in (60 cm)
Package 3 Length	31.50 in (80 cm)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>