NOTES:

1. MATERIAL AND FLAMMABILITY.
   POLYCARBONATE (LIGHT GRAY AND CLEAR) - UL94-HB
   BODY, COVER AND CLEAR COVER (C)
   FLAMMABILITY RATING (UL FILE #E41613)
   SERVICE TEMPUTER RANGE: -40°C TO +120°C

2. UL 508A (E352997) UL CERT OF COMPLIANCE.: BOXES UL LISTED
   NEMA TYPE 6P STANDARD. DESIGNED MEETS IP68 OF IEC529
   REQUIREMENTS. PC VERSION UV RESISTANT FOR OUT DOOR USE.

3. GASKET (NOT INSTALLED) MOLDED SILICONE WHITE

4. DIMENSIONS ARE INCH

GASKET (NOT INSTALLED)
MOLDED SILICONE WHITE

.09 [2.4]

∅.09 [2.2]

∅.18 [4.5]

∅.31 [8.0]

.12 [3.0]

DETAIL C
SCALE 3 : 1

9.45 [240.0]

4.49 [114.0]
4.49 [114.0]
4.25 [108.0]
4.25 [108.0]
3.97 [100.8]
3.97 [100.8]
3.03 [77.0]
3.03 [77.0]
2.24 [57.0]
2.24 [57.0]
1.46 [37.0]
1.46 [37.0]

A

2.68 [68.0]
2.91 [74.0]
1.48 [37.5]

6.30 [160.0]
4.60 [116.7]

1.48 [37.5]
2.68 [68.0]
2.91 [74.0]

.85 [21.6]

A

.50 [12.6]
3.98 [101.2]
3.98 [101.2]
.48 [12.3]

M3X6 TAPPING SCREWS X 21
(SCREWS NOT SUPPLIED)

M3X5 THREADED INERTS X 4
(SCREWS NOT SUPPLIED)

M4X25MM PAN
HEAD SCREWS X 6

BODY

3.01 [76.5]

SECTION A-A
SCALE 1 : 1.5

9.45 [240.0]
4.49 [114.0]
4.49 [114.0]

B

2.91 [74.0]

6.30 [160.0]

2.91 [74.0]

B

COVER

.59 [15.0] REF.

.12 [3.0]

SECTION B-B
SCALE 1 : 1.5

3.54 [90.0] REF.

DRAWING FOR REFERENCE
WE RESERVE THE RIGHT TO MAKE CHANGES TO OUR
STANDARD PRODUCTS. PLEASE CONSULT WITH BUD INDUSTRIES
PRIOR TO USING THIS DRAWING FOR DESIGN PURPOSE.