APPLICA	BLE STAN	DARD										
	OPERATING TEMPERATURE RANGE		_25°C TO +05°C			STORAGE TEMPERATURE RANGE			-25°C TO +60°C			
DATING	OPERATING&STORAGE HUMIDTY RANGE		85%MAX		APPLICABLE		E CABLE	<u> </u>	CABLE DIAMETER : φ6.6~7			
RATING	VOLTAGE											
	CURR	RENT										
		1	SPECI	IFIC <i>P</i>	ATIO	NS_				<u> </u>	1	
	UCTION		TEST METHOD			REQUIREMENTS				QT	AT	
	XAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.				X	Х	
MARKING		CONFIRMED VISUALLY.								Х	Х	
COUN			N OF REVISIONS		DESIGNED				CHECKED	DA	TE	
1 DREMARK			S-E-00003216			IKAWA	A D D D C	\/	TU. TANIGUCHI)1019	
THI			L BE MATED WITH DH40-27S				APPRO		KN. ICHIKAWA)1117	
OR DH3 * B-27S, IT AP DH3 * B-27S ABOUT A ENVIRONMENTAL CHA			ARACTERISTICS.			CHECKE			KN. ICHIKAWA	20091117		
							DESIGNED		MO. SHIMOYAMA	20091117		
Unless otherwise specified,						DRAWN		VN	TM. ONO)1117	
Note QT:Q	ualification Tes	st AT:Assu	urance Test X:Applicable T	est	DF	RAWIN	NG NO.		ELC-126587-00-00			
ж	SF	PECIFIC	ATION SHEET		PART NO.			DH-27-CV1B				
L/O	HIR	OSE ELI	ECTRIC CO., LTD.		CODE NO.		Cl	CL244-0010-5-00 🛕 1			1/1	