

WP 4185-WHPS - Web panel



1148690

<https://www.phoenixcontact.com/us/products/1148690>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Web panel with 47.0 cm / 18.5" TFT-display (projective-capacitive (PCAP)), 1366 x 768 pixel(s) (HD), 16.7 million colors, Arm[®] Cortex[®]-A53, 4x 1.2 GHz, 2x USB host 2.0, 1 x Ethernet (10/100 Mbps), RJ45, Yocto/Linux and user software: Chromium Browser. (bus system: without)

Your advantages

- Easy startup – just enter the IP and URL
- Flexible, thanks to open web standard and free choice of web server and visualization software
- No security updates are required for JAVA or Flash plug-ins thanks to HTML5
- Ideal for use with PLCnext Engineer or CODESYS
- Embedded Linux operating system
- Visualization of self-programmed JavaScript applications possible
- Secure communication, thanks to SSL-encrypted data transmission

Commercial Data

| | |
|--------------------------------------|---------------|
| Item number | 1148690 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales Key | DR17 |
| Product Key | DRCADF |
| GTIN | 4063151142346 |
| Weight per Piece (including packing) | 6,660 g |
| Weight per Piece (excluding packing) | 5,000 g |
| Customs tariff number | 84714100 |
| Country of origin | DE |

Technical Data

Product properties

| | |
|--------------|----------------|
| Product type | Operator panel |
|--------------|----------------|

Computer data

| | |
|---------------------|------------------------------|
| Processor | Arm® Cortex®-A53, 4x 1.2 GHz |
| Operating system | Yocto/Linux |
| RAM | 1 GB LPDDR3 |
| Data storage system | Flash eMMC, 8 GB |
| Slots | 1x microSD |

Display

| | |
|-----------------------|---------------------------------|
| Display type | 47.0 cm / 18.5" TFT |
| Screen resolution | 1366 x 768 Pixel(s) (HD) |
| Touch technology | projective-capacitive (PCAP) |
| Display lighting type | LED |
| Brightness | 240 cd/m², typical (adjustable) |
| MTBF | 50000 h |
| Color spectrum | 16.7 million colors |
| Reading angle left | 85 ° |
| Reading angle right | 85 ° |
| Reading angle top | 80 ° |
| Reading angle bottom | 80 ° |

Software

| | |
|---------------|------------------|
| User software | Chromium Browser |
|---------------|------------------|

System requirements

| | |
|----------------|------------------|
| Runtime system | Chromium browser |
|----------------|------------------|

Interfaces

| | |
|---------------------|----------------------------------|
| Interfaces | 2x USB Host 2.0 |
| Optional interfaces | Without optional interface |
| Network | 1 x Ethernet (10/100 Mbps), RJ45 |
| Bus system | without |

System properties

| | |
|---------------|------------------|
| User software | Chromium Browser |
|---------------|------------------|

System requirements

| | |
|----------------|------------------|
| Runtime system | Chromium browser |
|----------------|------------------|

Electrical properties

Supply

WP 4185-WHPS - Web panel



1148690

<https://www.phoenixcontact.com/us/products/1148690>

| | |
|-----------------------------|--------------------|
| Supply voltage | 24 V DC |
| Supply voltage range | 18 V ... 30 V |
| Power supply unit | 24 V DC \pm 20 % |
| Typical current consumption | 1.2 A |

Real-time clock

| | |
|----------------|-----------------------------|
| Realtime clock | Integrated (battery backup) |
|----------------|-----------------------------|

Mounting

| | |
|---------------|----------------|
| Mounting type | Front mounting |
|---------------|----------------|

Material specifications

| | |
|----------------------|-----------------------------|
| Material front plate | Aluminum (natural anodized) |
| Housing material | Steel sheet, zinc-plated |

Environmental and real-life conditions

Ambient conditions

| | |
|--|--------------------------------|
| Degree of protection | IP65 (front), IP20 (back) |
| Ambient temperature (operation) | 0 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 60 °C |
| Altitude | 3000 m |
| Permissible humidity (operation) | 20 % ... 85 % (non-condensing) |
| Permissible humidity (storage/transport) | 20 % ... 85 % (non-condensing) |
| Shock | DIN EN 60068-2-27 |
| Vibration (operation) | DIN EN 60068-2-6 |

Dimensions

External dimensions

| | |
|------------------------|--|
| Width / Height / Depth | 485 mm / 329 mm / 8 mm (Dimensions of the front plate) |
|------------------------|--|

Installation dimensions

| | |
|-------------------------------------|---|
| Width / Height / Installation depth | 475 mm / 311 mm / 53 mm (Installation cutout) |
|-------------------------------------|---|

1148690

<https://www.phoenixcontact.com/us/products/1148690>

Approvals



UL Listed

Approval ID: FILE E 238705



cUL Listed

Approval ID: FILE E 238705

1148690

<https://www.phoenixcontact.com/us/products/1148690>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27330201 |
| ECLASS-12.0 | 27330201 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC001412 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 43211900 |
|-------------|----------|

WP 4185-WHPS - Web panel

1148690

<https://www.phoenixcontact.com/us/products/1148690>



Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

WP 4185-WHPS - Web panel

1148690

<https://www.phoenixcontact.com/us/products/1148690>



Accessories

USB FLASH DRIVE - USB memory stick

2402809

<https://www.phoenixcontact.com/us/products/2402809>



USB memory stick, 8 GB

HMI SCB MOUNTING KIT 6 - Mounting material

2701385

<https://www.phoenixcontact.com/us/products/2701385>



HMI mounting kit for installation on a front plate. The mounting kit includes 6 x mounting brackets, 6 x screw threads, and a hexagonal wrench.

WP 4185-WHPS - Web panel

1148690


<https://www.phoenixcontact.com/us/products/1148690>



MC 1,5/ 3-STF-3,5 BD:1-3 - PCB connector

1751312

<https://www.phoenixcontact.com/us/products/1751312>




PCB connector, nominal cross section: 1.5 mm², color: green, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Tin, type of contact: Socket, number of potentials: 3, number of rows: 1, number of positions: 3, number of connections: 3, product range: MC 1,5/...-STF, pitch: 3.5 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, number of solder pins per potential: 1, plug-in system: COMBICON MC 1,5, locking: Screw locking, mounting: Screw flange, type of packaging: packed in cardboard

HMI WALL MOUNTING KIT - Mounting material

2701380

<https://www.phoenixcontact.com/us/products/2701380>

HMI mounting kit for panel installation. The mounting kit includes 2 spring clips.



1148690

<https://www.phoenixcontact.com/us/products/1148690>

MICROSDHC-16GB - Memory

1154696

<https://www.phoenixcontact.com/us/products/1154696>

Industrial grade 16 GB MicroSDHC 3DTLC



MICROSDHC-32GB - Memory

1154699

<https://www.phoenixcontact.com/us/products/1154699>

Industrial grade 32 GB MicroSDHC 3DTLC



Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com