

USB keyboard INT for 16:9 PRO devices, in stainless steel, RAL9006 (silver), with numerical keypad, inclination adjustable Further information, Quantity and content: see technical data



General information	
Product type designation	Stainless steel keyboard
Control elements	
Keyboard fonts	
<ul style="list-style-type: none"> • Design • Keyboard assignment • Color of the buttons • Color of the key inscription • Key illumination • Function keys <ul style="list-style-type: none"> — Number of function keys • Number pad • status LED displays <ul style="list-style-type: none"> — for number pad — for Shift keys 	Keyboard with short-stroke keys English Stainless steel Black No 12 Yes; Free-standing Yes; Num, Caps and Scroll Yes Yes
Connection type	
<ul style="list-style-type: none"> • USB • PS/2 • Cable length 	Yes; Type A No 1.5 m; Typical
Frame size/design	
<ul style="list-style-type: none"> • Standard • Ergonomic 	Yes; For industrial applications Yes; 90° adjustable / tiltable
Ergonomics	
<ul style="list-style-type: none"> • Trackball rest • Adjustable height 	No Yes; By adjusting inclination angle 0° to 90°
Installation type/mounting	
Mounting	Max. load bearing capacity of 2 kg
Mounting type	Suitable for PRO devices
Mounting position	Horizontal
maximum permissible angle of inclination without external ventilation	90°; Between 0° and 90° in steps of 15°
Supply voltage	
Design of the power supply	via USB
Input current	
Current consumption (rated value)	100 mA; Typical
Degree and class of protection	
IP (all-round)	IP65
Splashproof	Yes
Standards, approvals, certificates	

CE mark	Yes
BIS	No; required for export to India
RoHS conformity	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	45 °C
Operation (vertical installation)	
— For vertical installation, min.	0 °C
— For vertical installation, max.	45 °C
Operation (max. tilt angle)	
— At maximum tilt angle, min.	0 °C
— At maximum tilt angle, max.	45 °C
Operation (max. tilt angle, portrait format)	
— At maximum tilt angle, min.	0 °C
— At maximum tilt angle, max.	45 °C
Ambient temperature during storage/transportation	
• min.	0 °C
• max.	50 °C
Relative humidity	
• Operation, max.	80 %; no condensation
• Condensation permissible	No; Condensation not permissible
Operating systems	
Runs under operating system	
• Windows CE	Yes
• Windows Vista	Yes
• Windows XP	Yes
• Windows 7	Yes
• Windows 8	Yes
• Windows 10	Yes
Mechanics/material	
Material	
• Aluminum	Yes; Powder-coated, RAL 9006
• Stainless steel	Yes; Keyboard itself
Service life	
• Number of operating cycles, keys	10 000 000; Operations (minimum)
Dimensions	
Width	481 mm
Height	20 mm
Depth	171.6 mm
Weights	
Weight (without packaging)	3 700 g
Weight (with packaging)	5 300 g
Scope of supply	
Delivery quantity in pieces	1; With support arm bracket
Components included	a basic adapter is required for mounting, this must be ordered separately
Other	
Merchandise	Yes; Sasse no. 1580.9906433
Manufacturer name	Sasse Elektronik GmbH
Manufacturer's address	Berliner Straße 12, 91126 Schwabach, Germany
contacting the manufacturer	Phone +49 9122 978-0, e-mail: info@sasse-elektronik.de
Target devices	Merchandise suitable for 16:9 PRO devices
Note:	Successor 6AV688-10AU14-1DB0
last modified:	11/3/2021 