

Data sheet

3720.9 ZQI 4/2 RD



Insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 10.1 mm, Rated cross-section: 4 mm², Colour: Red

Business data

Article number	3720.9
Article name	ZQI 4/2 RD
GTIN (EAN)	4044211111427
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	1.32 g
Weight per piece (including packaging)	1.34 g
Unit of weight	G
Customs number	85389099
Country of origin	CZ
Prio-Article	3720.8
Product description	Insulated cross-connector

Technical data

Dimensions

Length	4.5 mm
Width	10.1 mm
Pitch size	6 mm

Ratings

Voltage with partition, max.	800 V
Voltage without partition, max.	800 V
Rated current	32 A
Rated cross-section	4 mm ²
Contamination degree	3

Connection data

No. of poles	2
--------------	---

Materials

Material	Copper alloy
Surface	Tin-plated
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

Further technical data

Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	2

Environmental Product Compliance

REACH Conform	yes
REACH Candidate Substance Note	No
RoHS Conform	yes

Media

Accessories

##INVERSE##CONTA-CONNECT



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3515.2</u>	ZRK 4/2A BG	4044211151751	100



Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1716.2</u>	ZRK 4/2A Ex BG	4044211058579	100



Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1717.2</u>	ZRK 4/3A Ex BG	4044211058609	100



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3516.2</u>	ZRK 4/3A BG	4044211151775	100



Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1718.2</u>	ZRK 4/4A Ex BG	4044211058630	100



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3517.2</u>	ZRK 4/4A BG	4044211151782	100