



TECHNICAL

LISTED: UL & CSA

RATED SUPPLY VOLTAGE: 120VAC

RATED CURRENT: UP TO 15 AMPS

RESET TYPE: MANUAL

OPERATING FREQUENCY: 60 Hz

TYPE: CLASS A

GROUND TRIP CURRENT: 4-6 mA

OVERLOAD CURRENT: 90 AMP 125 VAC

INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE

ENDURANCE OPERATIONS: 3000 OPERATIONS

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
	DIMENSION UNITS	SCALE	CURRENT REV DESC: MIGRATION TO ECTR/NX
$\nabla_A = 0$	INCH/MM	1:1	EC NO: 694247 DRWN: VBASUTHKARP 2022/02/02 CHK'D: DNGUYEN62 2022/02/14 APPR: HKNEELAND 2022/03/03 INITIAL REVISION: DRWN: TVICKERS 2009/09/01 APPR: DTITUS 2009/12/08
$\nabla_C = 0$	GENERAL TOLERANCES (UNLESS SPECIFIED)		
$\nabla_D = 0$	ANGULAR TOL $\pm 0.5^\circ$		
DIVISIONAL SYMBOLS	4 PLACES	\pm	
	3 PLACES	\pm	
	2 PLACES	\pm	
	1 PLACE	\pm	
	0 PLACES	\pm	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING SERIES
			D-SIZE 130135
DOCUMENT NUMBER		DOC TYPE	DOC PART
SD-130135-022		PSD	001
MATERIAL NUMBER		CUSTOMER	REVISION
1301530221		GENERAL MARKET	A1
DOCUMENT STATUS		RELEASE DATE	SHEET NUMBER
P1		2022/03/03 17:47:12	1 OF 1