




UDSK32-19-18-F

Ruland UDSK32-19-18-F, 1 3/16" x 1 1/8" Double Universal Joint, Friction Bearing, Steel, Set Screw With Keyway, 1.995" OD, 8.688" Length





Description

Ruland UDSK32-19-18-F is a double cardan friction bearing universal joint with 1.1875" x 1.1250" bores, 1/4" x 1/4" keyways, 1.995" OD, 8.688" length, and 3/8-16 set screws. It is ideal for applications with wide distances between shafts and can accommodate all forms of misalignment. This plain bearing double universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 90° when compared to commodity style double universal joints. UDSK32-19-18-F is made from high grade alloy steel for durability and high strength. It can be combined with boot UBOOT32/51-NI-KIT to protect the joints from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This double cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

P	roc	luct	Sne	cific	ation	2
	100	IUGL	JUC		auvii	Э.

Bore (B1)	1.1875 in	Small Bore (B2)	1.1250 in			
Keyway (K1)	1/4 in	Keyway (K2)	1/4 in			
B1 Max Shaft Penetration	1.700 in	B2 Max Shaft Penetration	1.700 in			
Joint Outer Diameter (OD)	1.995 in	Bore Tolerance	+0.0010 in / -0.0000 in			
Length (L)	8.688 in	Center Yoke Length (LC)	3.188 in			
Yoke Length (LY)	2.750 in	Hub Depth (LH)	1.700 in			
Broached Set Screw	3/8-16	Screw Finish	Black Oxide			
Peak Torque	19,350 in-lb	Rated Torque	3,870 in-lb			
Max Operating Angle	90°	Material Specification	Alloy Steel			
Manufacturer	Belden Universal	Country of Origin	USA			
Recommended Lubricant	LUBRIPLATE No. 1200-2	Matching Boot Cover	UBOOT32/51-NI-KIT			
UPC	63452932747	Tariff Code	8483.60.4000			
UNSPC	25173810					
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.					
Prop 65	▲WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov .					